

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit H, 1790' FNL & 1185' FEL
Section 35, T32N, R9W

5. Lease Designation and Serial No.

SF-079099-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 32 Fed Com 35

8. Well Name and No.

SJ 32 Fed Com35 #1

9. API Well No.

30-045-29587

10. Field and Pool, or exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other 7" casing
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

RIH w/8-3/4" bit & tagged cement @ 347'. Drilled cement from 347' to 380'. Drilled new formation to 3275'. Circulated hole. COOH. RIH w/7" 20# J-55 casing and landed @ 3200'. RU BJ to cement. Pumped 10 bbls mud flush and 10 bbls water first. Then pumped lead cement - 350 sx 65/35 POZ, 12% Gel (2.21 yield). Pumped tail cement - 150 sx Class B + 5#/sx Gil, 1/4#/sx flake & 2% CaCl2 (1.2 yield). Displaced with 128 bbls water; full returns, no cement to surface. Bumped plug @ 2000 psi 7/1/98.

NU WH & NU BOPs. RU Wilson to run temperature survey from 3115' to surface. Top of Cement @ 374'. RD Wilson. PT BOPs, WH & casing to 200 psi for 3 minutes and 2000 psi for 30 minutes. Good test.

14. I hereby certify that the foregoing is true and correct

Signed

Patsy Cluzton

Title

Regulatory Assistant

Date

7-6-98

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR

CORL

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

FARMINGTON DISTRICT OFFICE