Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993

٥.	Lease	Designatio	n and	Serial	No

	profit and company of the company of	SF-079148		
SUNDRY NOTICES AN	6. If Indian, Allottee or Tribe Name			
Do not use this form for proposals to drill				
Use "APPLICATION FOR	PERMIT - " for such proposals			
SUBMIT	IN TRIPLICATE DEVELOPED	7. If Unit or CA, Agreement Designation		
1. Type of Well	JUL 2 0 1998	San Juan 32 Fed Com 7		
Oil X Gas Other		8. Well Name and No.		
2. Name of Operator	SJ 32 Fed Com 7 #1			
Phillips Petroleum Company	OIL COLL DIV.	9. API Well No.		
3. Address and Telephone No.	DIST. 3	30-045-29585		
5525 Highway 64, NBU 3004, Farming	10. Field and Pool, or exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey De	escription)			
Unit K, 1509' FSL & 1522' FWL	Basin Fruitland Coal			
Section 7, T32N, R9W		11. County or Parish, State		
		San Juan, NM		
12. CHECK APPROPRIATE BOX(s	, OR OTHER DATA			
TYPE OF SUBMISSION				
Notice of Intent	Abandonment	Change of Plans		
 · ·	Recompletion	New Construction		
X Subsequent Report	Plugging Back	Non-Routine Fracturing		
	Casing Repair	Water Shut-Off		
Final Abandonment Notice	Altering Casing	Conversion to Injection		
	X Other/" Casing report	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)		
give subsurface locations and measured and true vert	pertinent details, and give pertinent dates, including estimated date of startical depths for all markers and zones pertinent to this work.)* 330'. Drilled cement from 330' to 388'. Dr			
	w/7" 20# casing and landed @ 3656'. RU BJ			

cement - 400 sx 65/35 (C1 H/POZ) with 5 #/sx Gilsonite, 1/4 #/sx Cello-flake, 12% gel mixed at 12 ppg with a yield of 2.21 cf/sx. Pumped tail - 150 sx C1 G with 5#/sx Gilsonite, 1/4 #/sx Cello-flake, 0.3% FL-52 & 2% CaCl2 mixed at 15.6 ppg with a yield of 1.2 cf/sx. Displaced with 147.8 bbls fresh water @ 2 - 4 bpm. Bumped plug @ 2000 psig at 2:53 hrs 6/17/98. Full returns, no cement to surface. Temperature Survey ran - Top of Cement @ 400'.

NU WH & BOPs. PT BOPs, WH & casing to 200 psi - 3 minutes and 1800 psi for 30 min. Good test.

				Jio Ramadi (53 JUL 26 7	15. 15. 15. 15. 15. 15.	
4. I hereby certify that the foregoing is true and correct Signed TONY T	Γitle	Regulatory Assistant	-	Date	6-24-98	8	_
(This space for Federal of State office use) Approved by	Title	·	ACUE	Date	/ a <u>r</u> .	กับ	_

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any makes, fictitious of foundations as to any makes within its invisdiction