

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

McElvain Oil & Gas Properties, Inc.

3. Address and Telephone No.

1050 17th Street, Suite 710 Denver, CO 80265 505-325-5220

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

790' FSL - 1500' FWL, Section 9, T32N, R10W, NMPM

5. Lease Designation and Serial No.

NM103367

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Brown No. 1R

9. API Well No.

30-045-29641

10. Field and Pool, or Exploratory Area

Blanco Mesa Verde

11. County or Parish, State

San Juan New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☒ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

September 5, 1998: Spud 12 1/4" surface hole at 6:45 PM. Drill to 373'. Run 8 jts. of 9 5/8", 36 ppf, J-55, ST&C casing with Halliburton cement nose guide shoe on bottom. Casing set at 365' KB. 9 5/8"x12 1/4" regular centralizers at 147', 234', & 342'. Cement with 220 sacks (259.6 CF) Class B cement with 3% CaCl2 and 0.25 pps cellflake. Circulate 5 bbls (24sxs) good cement to surface. Plug down @ 3:00 AM, 9/6/98. WOC 12 hours. Pressure test surface casing and BOPE to 600 psig for 30 minutes.

14. I hereby certify the foregoing is true and correct

Signed

Title Agent

Date October 21, 1998

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

OCT 23 1998

FARMINGTON DISTRICT OFFICE

BY