

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
McElvain Oil & Gas Properties, Inc.

3. Address and Telephone No.
1050 17th Street, Suite 710 Denver, CO 80265 505-325-5220

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
790' FSL - 1500' FWL, Section 9, T32N, R10W, NMPM

5. Lease Designation and Serial No.
NM103367

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No. *Red*
Brown No. 1R

9. API Well No.
30-045-29641

10. Field and Pool, or Exploratory Area
Blanco Mesa Verde

11. County or Parish, State
San Juan New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
- ☒ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☐ Other
- ☐ Change of Plans
- ☒ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

September 12, 1998: Drill 6 1/4" hole to 6250'. Run 57 jts. of 4 1/2", 10.5 ppf, J-55, ST&C casing with T1W LA set shoe on bottom and T1W L landing collar one joint up. Total casing 2524.59'. Set hanger at 3717'. Landing collar at 6205'. Casing shoe @ 6251'. Cement lead slurry of 186 sacks (332.9 cf) of 65/35 Class B Poz with 6% gel, 0.25 pps celloflake, and 0.3% TIC. Pump tail slurry of 100 sacks (115 cf) Class B with 0.25 pps. celloflake, 0.4% FLA and 0.1% retarder. Plug down @ 4:00 PM 9/13/98. Did not circulate cement off liner top.

14. I hereby certify the foregoing is true and correct

Signed

[Signature]

Title Agent

Date October 21, 1998

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

OCT 23 1998

ACCEPTED FOR RECORD

FARMINGTON DISTRICT OFFICE

BY