

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator


Roddy Production Company, Inc.

3. Address and Telephone No.

P.O. Box 2221, Farmington, NM 87499 (505) 325-5220

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

955' FNL - 1818 FWL, Section 19, T31N, R12W, NM



5. Lease Designation and Serial No.

SF078243

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Owen No. 2R

9. API Well No.

30-045-30235

10. Field and Pool, or Exploratory Area

Blanco Mesa Verde

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud 12 1/4" surface hole at 4:00 PM, 09/10/00. Drill to 331'. Run 7 joints (310.14') of 9 5/8" 36 ppf, J-55, ST&C, Paragon ERW casing with Howco cement nose guide shoe on bottom and 1-9 5/8" x 12 1/4" bowspring centralizer in middle of shoe joint. Set casing at 325' KB. Centralizers at 302'. Pump 10 bbl fresh water preflush. Cement with 200 sacks (222.0 cf) Class H with 3% CaCl and 0.25 pps celloflake. Mixed at 15.6 ppg to yield 1.11 cf/sk. Pumped at 3.5 BPM and 100-200 psi. Good circulation through out job. Displace with 23 bbls fresh water to 297'. Plug down at 5:45 AM, 09/11/00. Circulated 23 bbl (116 sacks) good slurry to surface. WOC 12 hrs. Nipple up BOPE. Pressure test to 600# for 30 minutes. Okay.

14. I hereby certify the foregoing is true and correct

Signed Robert E. Field

Title Business Agent

Date 09/25/00

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

