UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Name of Operator PLRICES OIL & GAS COMPANY Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700 Location of Well, Footage, Sec., T, R, M 1555'FSL, 1970'FEL, Sec.19, T-31-N, R-10-W, NMPM CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, Type of Submission Notice of Intent Abandonment Recompletion Y Subsequent Report Plugging Back Casing Repair Funal Abandonment Altering Casing X Other - Spud, casin TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csc sx Class "B" neat cmt w/3% calcium ch. (277 cu ft). Circ 15 bbl cmt to surfaces to 600 psi/30 min, OK. Drilling all APD ROW Related	REPORT, OTHER ion Change of Pl New Construction Non-Routine Water Shut of Conversion to the conversion	ans etion Fracturing off to Injection e clean. TOOH. Cmtd w/235 ops celloflake
Name of Operator **PURCLES** OIL & GAS COMPANY Address & Phone No. of Operator PO Box 47:89, Farmington, NM 87499 (505) 326-9700 Location of Well, Footage, Sec., T, R, M 1555'FSL, 1970'FEL, Sec.19, T-31-N, R-10-W, NMPM **CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, Type of Submission Notice of Intent X Subsequent Report Final Abandonment Final Abandonment Final Abandonment Type of Action Abandonment Recompletion Plugging Back Casing Repair Altering Casing X Other - Spud, casing X Other - Spud, casing TH W/5 jts 9 5/8" 32.3# H-40 ST&C csc sx Class "B" neat cmt W/3% calcium chi (277 cu ft). Circ 15 bbl cmt to surface csg to 600 psi/30 min, OK. Drilling all	REPORT, OTHER ion Change of Pl New Construct Non-Routine Water Shut of Conversion to ng, & cement 25'. Circ hole g, set @ 220'. loride, 0.25 p	Well Name & Number Crandell SRC #1C API Well No. 30-045-30405 Field and Pool Blanco MV/Basin DK County and State San Juan Co, NM DATA ans etion Fracturing off to Injection et clean. TOOH. Cmtd w/235 ops celloflake
Address & Phone No. of Operator PO Box 4:89, Farmington, NM 87499 (505) 326-9700 Location of Well, Footage, Sec., T, R, M 1555'FSL, 1970'FEL, Sec.19, T-31-N, R-10-W, NMPM CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, Type of Submission Notice of Intent Abandonment Recompletion X Subsequent Report Plugging Back Casing Repair Final Abandonment Altering Casing X Other - Spud, casin Check Appropriate Box To Indicate Nature Of Notice, Type of Action Abandonment Recompletion Altering Casing Tother - Spud, casin Altering Casing That Proposed or Completed Operations 2-10-01 MIRU. 2-11-01 Spud well @ 7:00 am 2-11-01. Drill to 2: TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csc sx Class "B" neat cmt w/3% calcium ch (277 cu ft). Circ 15 bbl cmt to surfac csg to 600 psi/30 min, OK. Drilling al	REPORT, OTHER ion Change of Pl New Construct Non-Routine Water Shut of Conversion to ng, & cement 25'. Circ hole g, set @ 220'. loride, 0.25 p	Well Name & Number Crandell SRC #1C API Well No. 30-045-30405 Field and Pool Blanco MV/Basin DR County and State San Juan Co, NM DATA ans ans ation Fracturing off to Injection c clean. TOOH. Cmtd w/235 aps celloflake
Location of Well, Footage, Sec., T, R, M 1555'FSL, 1970'FEL, Sec.19, T-31-N, R-10-W, NMPM CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, Type of Submission Notice of Intent X Subsequent Report Final Abandonment Final Abandonment Casing Repair Altering Casing X Other - Spud, casin Casing Repair Altering Casing X Other - Spud, casin TIH w/5 jts 9 5/8" 32.3# H-40 ST&C cscs sx Class "B" neat cmt w/3% calcium chicses csg to 600 psi/30 min, OK. Drilling all	REPORT, OTHER ion Change of Pl New Construct Non-Routine Water Shut of Conversion to ng, & cement 25'. Circ hole g, set @ 220'. loride, 0.25 p	Crandell SRC #1C API Well No. 30-045-30405 Field and Pool Blanco MV/Basin DK County and State San Juan Co, NM DATA ans ction Fracturing off to Injection c clean. TOOH. Cmtd w/235 ops celloflake
CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, Type of Submission Notice of Intent X Subsequent Report Plugging Back Casing Repair Final Abandonment Altering Casing X Other - Spud, casing X Other - Spud, casing X Other - Spud, casing TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csc sx Class "B" neat cmt w/3% calcium ch. (277 cu ft). Circ 15 bbl cmt to surface csg to 600 psi/30 min, OK. Drilling al	REPORT, OTHER ion Change of Pl New Construction Non-Routine Water Shut of Conversion to the conversion	Field and Pool Blanco MV/Basin DK County and State San Juan Co, NM DATA ans ction Fracturing off to Injection c clean. TOOH. Cmtd w/235 ops celloflake
Type of Submission Notice of Intent X Subsequent Report Final Abandonment X Other - Spud, casing 2-10-01 MIRU. 2-11-01 Spud well @ 7:00 am 2-11-01. Drill to 23 sx Class "B" neat cmt w/3% calcium chi (277 cu ft). Circ 15 bbl cmt to surface csg to 600 psi/30 min, OK. Drilling all	Change of Pl New Construction Non-Routine Water Shut of Conversion to the Conversion	ans etion Fracturing off to Injection e clean. TOOH. Cmtd w/235 ops celloflake
Notice of Intent X Subsequent Report Final Abandonment X Other - Spud, casin Describe Proposed or Completed Operations 2-10-01 MIRU. 2-11-01 Spud well @ 7:00 am 2-11-01. Drill to 22 TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csc sx Class "B" neat cmt w/3% calcium chi (277 cu ft). Circ 15 bbl cmt to surface csg to 600 psi/30 min, OK. Drilling all	Change of Pl New Construc Non-Routine Water Shut o Conversion t ng, & cement 25'. Circ hole g, set @ 220'. loride, 0.25 p	etion Fracturing off to Injection e clean. TOOH. Cmtd w/235 ops celloflake
X Subsequent Report Plugging Back Casing Repair Final Abandonment Altering Casing X Other - Spud, casing X Other -	Non-Routine Water Shut o Conversion t ng, & cement 25'. Circ hole g, set @ 220'. loride, 0.25 p	Fracturing off to Injection e clean. TOOH. Cmtd w/235 ops celloflake
Casing Repair Altering Casing X Other - Spud, casin Casing Repair Altering Casing X Other - Spud, casin Altering Casing Altering Casing Altering Casing Altering Casing Altering Casing	Water Shut o Conversion to the	e clean. TOOH. Cmtd w/235 cps celloflake
Z_Other - Spud, casing B. Describe Proposed or Completed Operations 2-10-01 MIRU. 2-11-01 Spud well @ 7:00 am 2-11-01. Drill to 22 TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csecons sx Class "B" neat cmt w/3% calcium child (277 cu ft). Circ 15 bbl cmt to surface csg to 600 psi/30 min, OK. Drilling all	ng, & cement 25'. Circ hole g, set @ 220'. loride, 0.25 p	e clean. TOOH. Cmtd w/235 ops celloflake
2-10-01 MIRU. 2-11-01 Spud well @ 7:00 am 2-11-01. Drill to 22 TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csc sx Class "B" neat cmt w/3% calcium chi (277 cu ft). Circ 15 bbl cmt to surfac csg to 600 psi/30 min, OK. Drilling al	g, set @ 220'. loride, 0.25 p	. Cmtd w/235 ops celloflake
2-11-01 Spud well @ 7:00 am 2-11-01. Drill to 22 TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csc sx Class "B" neat cmt w/3% calcium chi (277 cu ft). Circ 15 bbl cmt to surfac csg to 600 psi/30 min, OK. Drilling al	g, set @ 220'. loride, 0.25 p	. Cmtd w/235 ops celloflake
APD ROW Related		or. II bor w
·)		
igned May ale Title Regulatory		terepter con perner
		ACCEPTED FOR RECORD
This space for Federal or State Office use) PPROVED BY Title	Date	FFB 2 0 2001