

30-045-11119

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
BLM MAIL ROOM

## Sundry Notices and Reports on Wells

91 MAY 14 AM 11:10

1. Type of Well  
GAS

RECEIVED  
JUN 3 1991

5. Lease Number  
FARMINGTON AREA  
FARMINGTON, NEW MEXICO

6. If Indian, All or  
Tribe Name

2. Name of Operator  
Meridian Oil Inc.

OIL CON. DIV.  
DIST. 3

7. Unit Agreement Name

3. Address & Phone No. of Operator  
Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number  
Horton

9. API Well No.  
1

4. Location of Well, Footage, Sec, T, R, M.  
1043'S, 824'W Sec. 35, T-32-N, R-11-W, NMPM

10. Field and Pool  
Blanco Mesa Verde

11. County and State  
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA  
Type of Submission

## Type of Action

☒ Notice of Intent

☒ Abandonment

☐ Change of Plans

☐ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut Off

☐ Altering Casing

☐ Conversion to Injection

☐ Other

13. Describe Proposed or Completed Operations

It is intended to plug and abandon this well in the following manner:

MOL&RU. ND WH. NU BOP. TOO H w/pkr & 2 3/8" tbg. Ran CBL 4440-surface. TIH, set cmt ret @ 4430'. PT tbg. Cmt squeeze below ret w/285 sx (336 cu.ft.) cmt. Pull out of ret & spot 15 sx (17 cu.ft.) cmt 4430-4380'. Circ hole w/9.0 ppg mud. Perf 4 squeeze holes @ 2320'. TIH w/cmt ret set @ 2300'. Squeeze cmt w/21 sx cmt below ret to cover 50' over top of Fruitland. Spot 15 sx (17 cu.ft.) cmt on top of ret to cover top of FT inside csg 2300-2250'. Spot 29 sx cmt (34 cu.ft.) 1880-1780' to cover 100' across squeeze holes. Spot 29 sx (34 cu.ft.) cmt 1070-970' to cover 100' across Ojo Alamo. Perf 4 squeeze holes 20' above TOC  $\pm$  800'. Set cmt ret @ 200'. Perf 4 circ holes @ 190'. Squeeze w/156 sx cmt (184 cu.ft.) from 800' to 190' to cover Nacimiento. TOO H w/tbg as soon as cmt is pumped. (Note: due to 1963 bradenhead squeeze, as well as above Nacimiento squeeze, it is not possible to cover surface csg shoe-open hole annulus w/cmt.) Circ 58 sx (64 cu.ft. cmt from ret @ 200' to surface. Cut off WH. Install dry hole marker.

SEE ATTACHED FOR  
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Regulatory Affairs Date 5/14/91

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_

CONDITION OF APPROVAL, IF ANY:

MAY 30 1991  
DATE

AREA MANAGER