
Form 9-881 a (Feb. 1961)

TEXAS



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land	Office .	Senta Fe
Lease	No	078137
Unit .		



SUNDRY NOTICES AND REPORTS ON WELLS

		1 0
NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF U.S. CECLECION
NOTICE OF INTENTION TO CHANG	GE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST		SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DR		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.
NOTICE OF INTENTION TO SHOOT		SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL (Subsection Report - Surface Casing
NOTICE OF INTENTION TO ABAND	DON WELL	
(ine	DICATE ABOVE BY CHECK MAP	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
		December 23, 195
	ocated 660 ft. from	(Al) toda (F)
(14 Sec. and Sec. No.)	, }%6.# \ (Twp.)	(Range) (Meridian)
(M Sec. and Sec. No.)	San June	and the second s
(Field)	(Count	ty or Subdivision) (State or Territory)
	hs to objective sands; show a ing points, and al	AILS OF WORK sizes, weights, and lengths of proposed casings; indicate mudding jobs, com- ll other important proposed work)
ell spudded Decembe eints - 183° of 10- lus 2% Cm Cl. Cem	er 19, 1959 at 1 3/4" 32.75/ Heigent tent of the control of the c	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cem
ell spudded Decembe eints - 183' of 10- lus 2% Cm Ci. Ceme O. WOC Righters.	er 19, 1959 at 1 3/4" 32.75/ Heigent tent of the control of the c	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) 12:15 PM. Drilled 15" hole to 195'. Ran 6 10 casing. Cemented with 225 sex regular to surface. Plug down at 3:15 PM December
ell spudded Decembe bints - 183° of 10- lus 2% Cm Ci. Ceme Co. WOC Righters. 1 -1/lim bit.	er 19, 1959 at 1 -3/li* 32.75/ Hei ent circulated t	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) 12:15 PM. Drilled 15" hole to 195'. Ran 6 10 casing. Cemented with 225 sex regular to surface. Plug down at 3:15 PM December
ell spudded Decembe bints - 183° of 10- lus 2% Cm Ci. Ceme 10. WOC Righters. T i-1/li" bit.	er 19, 1959 at 1 -3/1; 32.75/ Heigent circulated t Tested casing wi	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) 12:15 PM. Drilled 15" hole to 195'. Ram (10 casing. Cemanted with 225 sax regular to surface. Plug down at 3:15 PM December ith 500% for 15 min. Held OK. Drilled out
lunderstand that this plan of the company TEXAS MATE	er 19, 1959 at 1 -3/1; 32.75/ Heigent circulated t Tested casing wi	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) 12:15 PM. Drilled 15" hole to 195'. Ran (D casing. Casanted with 225 sax regular to surface. Plug down at 3:15 PM December ith 500% for 15 min. Held OK. Brilled out
ell spudded December of 10 ius 2% Ca Cl. Ceme 10. WOC 21d hrs. Tunderstand that this plan of the company TEXAS MATE address 908 South (er 19, 1959 at 1 er 19, 1959 at 1 -3/1; 32.75/ Heigent circulated to the community of the control of the cont	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) 12:15 PM. Drilled 15" hole to 195'. Ran (D casing. Casanted with 225 sax regular to surface. Plug down at 3:15 PM December ith 500% for 15 min. Held OK. Brilled out
ell spudded December of 10 to	er 19, 1959 at 1 er 19, 1959 at 1 -3/1; 32.75/ Heigent circulated to the community of the control of the cont	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) 12:15 PM. Drilled 15" hole to 195'. Ran (D casing. Casanted with 225 sax regular to surface. Plug down at 3:15 PM December ith 500% for 15 min. Held OK. Brilled out
ell spudded December of 10 lue 2% Ca Cl. Ceme 10. WOC 21d has. The bit. I understand that this plan of the company TEXAS MATER address 908 South (er 19, 1959 at 1 er 19, 1959 at 1 -3/1; 32.75/ Heigent circulated to the community of the control of the cont	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemil other important proposed work) 12:15 PM. Drilled 15" hole to 195'. Ram (10 casing. Cemanted with 225 sax regular to surface. Plug down at 3:15 PM December ith 500% for 15 min. Held OK. Drilled out