


(SUBMIT IN TRIPLICATE)



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency -----
Navajo - Ute
Allottee **Mountain Tribal**
Lease No. **14-20-600-2540**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	XI
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	Perforating & Fracturing	XI

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hobbs, New Mexico July 19, 19**63**

Navajo "P"
Well No. **6** is located **640** ft. from **[S]** line and **640** ft. from **[E]** line of sec. **35**
SE/4 SE/4 Sec. 35 **32-W** **17-W** **N.M.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undesignated Gallup **San Juan** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **5401** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well spudded June 18, 1963. Set 7-5/8" OD casing at 27' and cemented with 10 sacks by hand. W.O.C. 2 1/2 hrs. Drilled to 1168'.

CORE NO. 1 - 1168 - 1206' - Recovered 20'

- Top - 2' - Broken sand and shale
- Next - 8' - Dark gray shale
- Next - 3' - Sandy shale
- Next - 4' - Gray medium sand, hard and tight, No shows
- Next - 1' - Black shale, slightly sandy
- Next - 1' - Sandy shale
- Last - 1' - Medium gray silty sand

Drilled from 1206' to 1307'.

(See Reverse Side)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Shelly Oil Company**

Address **Box 790**

Hobbs, New Mexico

(ORIGINAL SIGNED) **H. E. Aab**

By

Title **Dist. Supt.**



WELL NO. 2 - 1907 - 1927 - RECORDED 1941

Top - 5' - 6" - Medium gray sandstone, all extracted
Next - 13' - 0" - Sandy shale

Reached total depth of 1360' on June 22, 1963. Set 4-1/2" OD casing at 1377' and cemented with 75 sacks, W.O.C. 24 hrs. Sand OK tested OK. Did not drill out cement plug at 1335' P.M. I.D. 1335'. Perforated 7-5/8" OD casing from 1303-1310' for a total of 7' and 28 holes. Treated through 7-5/8" OD casing ports. 1303-1310' with 30,000 gallons loose oil and 30,000 gal. After recovering all load oil well pumped 132 holes. of oil in 24 hours.