

10	11	12
13	14	15
16	17	18



(SUBMIT IN TRIPLICATE)

 UNITED STATES
 DEPARTMENT OF THE INTERIOR
 GEOLOGICAL SURVEY
Indian Agency Navajo TribalAllottee Navajo "H"Lease No. 14-20-403-5013

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	XX
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Perforate & Fracture	XX

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 26, 1963

Navajo "H"
 Well No. 8 is located 1980 ft. from N line and 775 ft. from E line of sec. 34
SE/4 NE/4 Sec. 34 32-N 17-W N.M.P.M.
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Horseshoe Gallup San Juan New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5499 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well spudded April 1, 1963. Set 8-5/8" OD casing at 31' and cemented with 10 sacks by hand. W.O.C. Drilled to 1720',

Core No. 1 - 1720' - 1780' (20') - Recovered 20'
 Top - 10' - 6" - Black shale with sand stringers
 Next - 6' - 0" - Sandstone, Med. grained with carbon streaks, all 6' oil saturated
 Next - 3' - 6" - Black shale with streaks of lime

Reached total depth of 1780' on April 4, 1963. Set 5-1/2" OD casing at 1775' and cemented with 75 sacks. W.O.C. 24 hrs. Shut off tested OK. Did not drill out cement plug at 1759'. P.B.T.D. 1759'. Perforated 5-1/2" OD casing from 1732-1738' for a total of 6' and 24 holes. Treated through 5-1/2" OD casing perfo. 1732-1738' with 19,614 gals. lsc. oil and 25,000# 20/40 sand & 12 ball sealers. (See Reverse Side)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shelly Oil CompanyAddress Box 38Hobbs, New MexicoBy (ORIGINAL SIGNED) H. E. AabTitle Dist. Supt.

After receiving all lead all jumped 72 barrels of oil to 24 barrels