	Form (A)	n 9- 8 pril 19	331 b 52)	
-				

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency
erajo Tribal
Allottee Karaje
Lesse No. 14-20-603-501

NOTICE OF INTENTION TO DRILL	su	BSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS	su	BSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	su	BSEQUENT REPORT OF ALTERING CASING
IOTICE OF INTENTION TO REDRILL OR REPAIR WELL	su	BSEQUENT REPORT OF REDRILLING OR REPAIR.
OTICE OF INTENTION TO SHOOT OR ACIDIZE	su	BSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	su	PPLEMENTARY WELL HISTORY.
NOTICE OF INTENTION TO ABANDON WELL	X	
(INDICATE ABOVE BY CHEC	K MARK NATURE	OF REPORT, NOTICE, OR OTHER DATA)
	44401114-	July 31, , 19. 59
II No. A Salanta J 2330	4 C [N]	line and 3330 ft. from E line of sec. 33
eli INO is located	It. Irom	line and the it, from the or sec.
(% Sec. and Sec. No.) (Twp.)	(Range)	(Meridian)
(Mast. and Sec. No.) (1wp.)	(Range)	(Maciciali)
(Field)	(County or Subdiv	rision) (State or Territory)
e elevation of the derrick floor above		
ate names of and expected depths to objective sands:		
ing nointe	show sizes, weigh	ats, and lengths of proposed casings; indicate mudding jobs, coment-
ing points,	show sizes, weigh and all other imp	ats, and lengths of proposed casings; indicate mudding jobs, cement- cortant proposed work)
ing points,		
is well has been drilled to a	Total Dep	
de well has been drilled to a	Total Depi	th of 1250° and fully tested without
is well has been drilled to a countering any commercial cil 35° - 1115° with 15 seeks com 11 44°00 cosing, will set 25 0	Total Depi of gas po mb. Vill and compa	th of 1250° and fully tosted without y. Well to be plugged as follows: Fun free point indicator, out off and t plug where easing is out off. 5 sock
is well has been drilled to a secunioring any commercial oil 35' - 1115' with 15 sacks com 11 44'00 casing, Mill set 25 ment plug to be set in top of	Total Depi of gas po mb. Vill and compa	th of 1250° and fully tosted without y. Well to be plugged as follows: Fun free point indicator, out off and t plug where easing is out off. 5 sock
is well has been drilled to a secuntaring any commercial oil 1951 - 11157 with 15 seeks com 11 44°00 coning. Will set 25 0	Total Depi of gas po mb. Vill and compa	th of 1250° and fully tosted without y. Well to be plugged as follows: Fun free point indicator, out off and t plug where easing is out off. 5 sock
is well has been drilled to a secuntaring any commercial oil 35° - 1115° with 15 seeks com 11 A4°60 century. Will set 25 a ment plug to be set in top of tending A' above ground level.	Total Depi of gas po mb. Vill : mak comes 3-5/8*00 (th of 1250° and fully tosted without y. Well to be plugged as follows: Fun free point indicator, out off and t plug where easing is out off. 5 sock parface casing with 4" pipe marker
is well has been drilled to a countering any commercial oil 35° - 1115° with 15 sacks com 11 44°60 casing, Mill oot 25 ment plug to be set in top of	Total Depi of gas po mb. Vill : mak comes 3-5/8*00 (th of 1250° and fully tosted without y. Well to be plugged as follows: Fun free point indicator, out off and t plug where easing is out off. 5 sock parface casing with 4" pipe marker
is well has been drilled to a countering any commercial cil 35° - 1115° with 15 sacks com 11 Ad 60 casing, Will set 25 count plug to be set in top of tending A' above ground level.	Total Depi of gas po mb. Vill : mak comes 3-5/8*00 (th of 1250° and fully tested without y. Well to be plugged as follows: Fun free pedra indicator, out off and t plug where easing is out off. 5 suck surface easing with 4" pipe marker work by Phil Medrath.
is well has been drilled to a esuntering any commercial cil 35° - 1115° with 15 seeks com 11 44°00 century. Will set 25 a ment plug to be set in top of tending 4° above ground level.	Total Depi of gas po mb. Vill : mak comes 3-5/8*00 (th of 1250° and fully tested without y. Well to be plugged as follows: Fun free pedra indicator, out off and t plug where easing is out off. 5 suck surface easing with 4" pipe marker work by Phil Medrath.
is well has been drilled to a secuntaring any commercial oil (35° - 1115° with 15 seeks com 11 A4°(0 century, Will set 25 century to be set in top of stending 4° above ground level.	Total Depi of gas po mb. Vill : mak comes 3-5/8*00 (th of 1250° and fully tested without y. Well to be plugged as follows: Fun free pedra indicator, out off and t plug where easing is out off. 5 suck surface easing with 4" pipe marker work by Phil Medrath.
is well has been drilled to a countering may commercial oil 35° - 1115° with 15 sacks com 11 Ag*(0 casing, Mill set 25 ment plug to be set in top of tending A° above ground level rbal approval has been given to	Total Depi or gas pa mt. Will i mak comes 3-5/8*00 i	th of 1250° and fully tested without y. Wall to be plugged as follows: Fun free paint indicator, out off and a plug where easing is out off. 5 most surface easing with 4° pipe marker work by Phil McGrath.
is well has been drilled to a countering any commercial oil 35° - 1115° with 15 sacks com 11 Ad 60 casing, Mill set 25 cast plan to be set in top of tending A' above ground level rbal approval has been given to	Total Depi or gas pa mt. Will i mak comes 3-5/8*00 i	th of 1250° and fully tosted without y. Well to be plugged as follows: Fun free point indicator, out off and t plug where easing is out off. 5 sock parface casing with 4" pipe marker
is well has been drilled to a countering any commercial cil 35° - 1115° with 15 sacks com 11 Ag*(0) casing, Mill set 25 (ment plug to be set in top of tending A* above ground level. That approval has been given the lapproval has been given to be a given	Total Depi or gas pto mt. Vill : lask comes 3-5/8°CD :	th of 1250° and fully tested without y, Wall to be pingged as foliamer Fun free paint indicator, out off and a ping where easing is out off. 5 suck surface easing with 4" pipe marker want by Phil McGrath. 959 co
de well has been drilled to a countering any commercial cil. 35' - 1115' with 15 sacks commercial cil. 11 Af'() casing, Will cet 25 (ment plug to be set in top of tending A' above ground level. The approval has been given to the approval to the approval has been given to the approval to the approval has been given to the approval to the approval has been given to the approval to the approval has been given to the approval to the approval has been given to the approval to the approval to the approval has been given to the approval to t	Total Depi or gas pa mt. Will inst comes 3-5/8*CD	th of 1250° and fully tested without y, Wall to be pingged as foliamer Fun free paint indicator, out off and a ping where easing is out off. 5 suck surface easing with 4" pipe marker want by Phil McGrath. 959 co
is well has been drilled to a countering my commercial cil. 35' - 1115' with 15 sacks com 11 Af'() casing, Will set 25 (ment plug to be set in top of tending A' above ground level. That approval has been given to the same of the sa	Total Depi or gas pa mt. Will inst comes 3-5/8*CD	th of 1250° and fully tested without y, Wall to be pingged as foliamer Fun free paint indicator, out off and a ping where easing is out off. 5 suck surface easing with 4" pipe marker want by Phil McGrath. 959 co
is well has been drilled to a countering any commercial cil. 35' - 1115' with 15 sacks com 11 Ad'() casing, will set 25 (ment plug to be set in top of tending A' above ground level. The approval has been given to	Total Depi or gas pa mt. Will inst comes 3-5/8*CD	th of 1250° and fully tested without y. Wall to be plugged as follows: Fun free paint indicator, out off and a plug where casing is out off. 5 suck surface casing with 4° pipe marker work by Phil McGrath. 959 CO by the Geological Survey before operations may be commenced.
is well has been drilled to a countering any commercial cil. 35' - 1115' with 15 sacks com 11 Ad'() casing, will set 25 (ment plug to be set in top of tending A' above ground level. The approval has been given to	Total Depi or gas pa mt. Will inst comes 3-5/8*CD	th of 1250° and fully tested without y, Wall to be pingged as foliamer Fun free paint indicator, out off and a ping where easing is out off. 5 suck surface easing with 4" pipe marker want by Phil McGrath. 959 co
de well has been drilled to a securitering any commercial cil. 35' - 1115' with 15 sacks can all 45'(0 casing, will set 25') ment plug to be set in top of stending 4' above ground level. The approval has been given to be approval has been given to be approval has been given to be approval approval has been given to be approval has been given to be approval approval has been given to be approved that this plan of work must receive approval.	Total Depi or gas pa mt. Will inst comes 3-5/8*CD	th of 1250° and fully tested without y. Wall to be plugged as follows: Fun free paint indicator, out off and a plug where casing is out off. 5 suck surface casing with 4° pipe marker work by Phil McGrath. 959 CO by the Geological Survey before operations may be commenced.