

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

RECEIVED  
BLM

5. Lease Designation and Serial No.  
H-20-603-5013

6. If Indian, Allottee or Tribe Name

Navajo

7. If Unit or CA, Agreement Designation

Navajo "M"

8. Well Name and No.

M-2

9. API Well No.

3004512000051

10. Field and Pool, or Exploratory Area

Many Rocks C

11. County of Parish, State

San Juan N.M.

SUBMIT IN TRIPLICATE

070/FARMINGTON, NM

1. Type of Well

☐ Oil Well

☐ Gas Well

☒ Other injection Well

2. Name of Operator

APA Development, Inc.

3. Address and Telephone No.

P.O. Box 215 Cortez, CO. 81321 (303)565-2458

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980 FSL 1980 FWL Sec 33 T32N R17W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plan to plug well as follows:

1. latch out of Model D packer and equalize cement plug from 1246' to 1106'
2. Pick up to 800' place cement plug inside and outside 5 1/2" casing stub
3. Pick up to 750' circulate hole to 50' with inhibited water
4. cement 50' to surface
5. Weld on dry hole marker on 8 5/8" casing, clean and remediate location

14. I hereby certify that the foregoing is true and correct

Signed

Pat & W. W. W. W.

Title

SEE ATTACHED FOR

Date

10/14/99

(This space for Federal or State office use)

CONDITIONS OF APPROVAL

Approved by

Conditions of approval, if any:

Title

Date

APPROVED

OCT 25 1999

WETZELMANAGER

\*See Instruction on Reverse Side

NMOOD

INFORMATION ON THE  
RECORDS OF THE

RECORDS OF THE  
RECORDS OF THE  
RECORDS OF THE