

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

A.P.A. Development, Inc.

3. Address and Telephone No.

P.O. Box 215 Cortez, CO 81321 (970) 565-2458

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

560 FNL 2180 FWL Sec. 34, T32N, R17W

5. Lease Designation and Serial No.

14-20-603-5013

6. If Indian, Allottee or Tribe Name

Navajo

7. If Unit or CA, Agreement Designation

Navajo M

8. Well Name and No.

M-12

9. API Well No.

30045112130051

10. Field and Pool, or Exploratory Area

Many Rocks

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

April 26, 1996

1. Tagged PSTD at 1237', Pumped 35 sk cement
2. let Set for 2 1/2 hrs.
3. Tagged cement top at 901'
4. TOH with tubing, TIH with packer, isolated casing leak at 166'
5. TOH with packer, ran perforating gun, shot 3 squeeze holes at 200'
6. TIH with packer, set at 190', pumped 54 sk cement inside and outside 4 1/2" casing. TOH with tubing, cut off wellhead, topped inside and outside casing with cement.

14. I hereby certify that the foregoing is true and correct

Signed Pat Woolley

Title

Date 11/29/96

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

APPROVED

MAY 17 1996