

(SUBMIT IN TRIPLICATE)

Indian Agency **NAVAJO TRIBAL**

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee _____

Lease No. **14-20-603-5012**

	27	
		X

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

JANUARY 23, 19 **63**

Well No. **NAVAJO 3-27-X** is located **625** ft. from **[N]** line and **2000** ft. from **[E]** line of sec. **27**

SW SE 27 (34 Sec. and Sec. No.) **32N 17W** (Twp.) **NWP** (Range) **NWP** (Meridian)


UNDESIGNATED (Field) **SAN JUAN** (County or Subdivision) **NEW MEXICO** (State or Territory)

The elevation of the derrick floor above sea level is **5915** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 1768' of 5" J-55, 11 1/2# with 25 sx casing. Perforated 1713-1726 (7') with 4 jet shots per ft. Sand oil fractured with 640 bbls oil and 15,000# sand. Broke down at 2800 psi, treated at 1500 psi with injection rate of 22 bbls/min. Ran 1720' of 2" tubing and installed pump on January 13, 1963. Pumped all load oil and gauged new oil at the average rate of 102 BOPD on a 24 hour gauge.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **CURTIS J. LITTLE**

Address **2929 MONTE VISTA, NE**
ALBUQUERQUE, NEW MEXICO

By *Curtis J. Little*
Title **OPERATOR**