


(SUBMIT IN TRIPLICATE)

Indian Agency Winona Rock

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee _____

Lease No. 3-419-221-1950



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL		

RECEIVED

JUN 30 1950

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL

WINONA ROCK, NEW MEXICO

Well No. 1 is located 720 ft. from S line and 135 ft. from E line of sec. 35
1/4 Sec. and Sec. No. 1/4 Sec. 1/4 Sec. 1/4 Sec.
Winona Rock San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5298 ft. (Ungrated Ground)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total Depth 1616'. Run logs. Tops of formations are as follows: Lower Gallup - 900', San Juan - 1115'.

Logged 39 fte, 1193', of 4 1/2" casing at 1193' with 75 cu. cement. Top cement at 925'.

Drilled cement plug 6/21/50. Tested for 2 hours with 500# pressure pump.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company ATCO OIL & GAS COMPANY

Address Box 104

WINONA ROCK, NEW MEXICO

By ORIGINAL SIGNED BY JOE C. SALMON

Title JOE C. SALMON
1513001 SUPERVISOR



