

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-600-3539

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo-Ute Mountain

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo-Ute Mountain

9. WELL NO.

#12-26

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND

SURVEY OR AREA

SW 1/4 Section 26

T32N, R17W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER

Dry Hole

2. NAME OF OPERATOR

The Superior Oil Company

3. ADDRESS OF OPERATOR

P. O. Drawer 'G', Cortes, Colorado

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)

At surface

698' FNL and 2090' FNL of section 26

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5920' GD, 5932' KB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plugged and abandoned well on September 22, 1964 at 1872' T.D. as follows:

Plug #1: Placed 28 sacks common cement in bottom of 6-3/4" air drilled hole.

Filled hole with water.

Plug #2: Placed 10 sacks common cement in top of 3-5/8" surface casing.

Welded plate to casing stub and erected standard dry hole marker.

RECEIVED

OCT 1 1964

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

J. C. GORDY

SIGNED

J. C. Gordy

TITLE

Drilling Engineer

DATE

Sept. 30, 1964

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JCG/njh

\*See Instructions on Reverse Side