

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Sundry Notices and Reports on Wells

RECEIVED
97 APR 29 PM 2:37
070 FARMINGTON, NM

1. Type of Well
Oil

2. Name of Operator

Texas Pacific Oil & Gas Co., C/O Joseph E. Seagram & Sons, Inc.

3. Address & Phone No. of Operator

800 3rd Ave., New York City, NY 10022-7699

4. Location of Well, Footage, Sec., T, R, M

1360' FNL and 260' FWL, Sec. 27, T-32-N, R-17-W, NMPM
E

5. Lease Number
14-20-603-5012
6. If Indian, All. or
Tribe Name
Navajo
7. Unit Agreement Name
N/A
8. Well Name & Number
Navajo #11
9. API Well No.
045-11295
10. Field and Pool
Many Rocks
11. County & State
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

Texas Pacific Oil & Gas Co., plugged and abandoned this well on April 16, 1997 per the attached Plug & Abandonment report.

14. I hereby certify that the foregoing is true and correct.

Signed

William F. Clark
William F. Clark, President A-Plus Well Service

Title

Contractor

Date

4/28/97

(This space for Federal or State Office use)

APPROVED BY

William F. Clark

Title

Contractor

Date

MAY 01 1997

CONDITION OF APPROVAL, if any:

A - PLUS WELL SERVICE, INC.

P.O. BOX 1979
FARMINGTON, NM 87499
505-325-2627 • FAX: 505-325-1211

RECEIVED
BLM

97 APR 29 PM 2:37

Texas Pacific Oil & Gas Co.,
c/o Joseph E. Seagram & Sons

Navajo #11

1360' FNL and 260' FWL, Sec. 27, T-32-N, R-17-W,
San Juan County, NM
BIA 14-20-603-5012

April 25, 1997

070 FARMINGTON, NM

Plug & Abandonment Report

Cementing Summary:

Plug #1 mix and pump 50 sxs Class B cement down 2-7/8" casing to 1640' into Gallup perforations and to cover top, displace to 300'.

Plug #2 with 91 sxs Class B cement pumped down 2-7/8" casing from 325' to surface to cover base of Mesaverde, circulate 1 bbl good cement to surface.

Plugging Summary:

Notified BLM on 4/15/97

- 4-15-97 Safety Meeting. Road cement equipment to location and RU. Establish rate down 2-7/8" casing with 10 bbls water, 1 bpm at 1000# with no blow out bradenhead. Plug #1 mix and pump 50 sxs Class B cement down 2-7/8" casing to 1640' into Gallup perforations and to cover top, displace to 300'. Shut in well and WOC overnight. RD equipment and move to Navajo #1.
- 4-16-97 Safety Meeting. Open up well, no pressures. Pressure test casing to 300#; held OK. RU A-Plus wireline truck and RIH; tag cement at 325'. Perforate 2 squeeze holes at 300'. Establish circulation down 2-7/8" casing and out 7-5/8" with 10 bbls water. Plug #2 Shut in well and WOC. Dig out wellhead. Cut wellhead off; found cement at surface in casing and annulus. Mix 5 sxs Class B cement and install P&A marker. RD cement equipment and move off location.
J. Sanchez, BLM representative was on location.