

Form C-122

Revised 12-1-55

Pool 11-60 Formation 11-60 County 11-60

Initial 1 Annual Special Date of Test 9/1/85

Company Archer Oil and Gas Company Lease Archer - 1000 Well No. 10

Unit 1 Sec. 3 Twp. 2 Rge. 3 Purchaser _____

Casing 7 Wt. 22 D. 2.375 Set at 1571 Perf. 1522 To 1575

Tubing 1 1/2 Wt. 1.7 I.D. 1.2 Set at 1000 Perf. 100 To 100

Gas Pay: From 1-1-00 To 1-1-01 L xG -GL Bar.Press.

Producing Thru: Casing _____ Tubing 1 _____ Type Well 2 _____

Date of Completion: 1/1/55 Packer Reservoir Temp.

OBSERVED DATA

Tested Through (Prover) (Choke) (Meter) Type Taps _____

[illegible]

No.	Coefficient (24-Hour)	$\sqrt{h_{wPf}}$	Pressure psia	Flow Temp. Factor F_t	Gravity Factor F_g	Compress. Factor F_{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.46		120	1.00	1.00	1.07	1.06
2.							
3.							
4.							
5.							

as Liquid Hydrocarbon Ratio _____ cf/bbl. Specific Gravity Separator Gas _____
 Gravity of Liquid Hydrocarbons _____ deg. Specific Gravity Flowing Fluid _____
 c. _____ (1-e⁻⁵) P_c 1019 P_c 1019

[illegible]

Absolute Potential: 0.00 MCFPD; n 1

COMPANY Arden Electronics
ADDRESS 10000 Wilshire Blvd

ADDRESS 6074, Fairview, New York

AGENT and TITLE ORIGINAL SIGNED BY D. K. BRYANT

WITNESSED _____
COMPANY _____

COMPANY	REMARKS

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressability factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received <u>3</u>		
DISTRIBUTION		
	NO. FURNISHED	
Operator	1	
County Rep		
Engineering Dept		
Production Dept	1	
Geology Dept		
Inspector	1	✓
Other		