SA. Indicate Type of Lease STATE ST	SANTA FE /		WEXICO OIL CONSEK	VATION COMMISSION		orm C-101	
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well DEEPEN APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Well APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK PROPOSED CASING AND THE SOUTH T					_		Type of Logge
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Property of Work Deepen Property Pro	FILE /	_ 				_	
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Wint DEEPEN DEEPEN DEEPEN PLUG BACK TO CHILL DEEPEN DEEPEN PLUG BACK TO CHILL DEEPEN ATTER OF WINT APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK TO CHILD DEEPEN ATTER OF WINT APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK TO CHILD DEEPEN ATTER OF WINT APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK TO CHILD DEEPEN APPLICATION FOR WINTER APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK TO CHILD DEEPEN APPLICATION FOR WINTER APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK TO CHILD DEEPEN APPLICATION FOR WINTER APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK TO CHILD DEEPEN TO CHILD DEEPE					<u>_</u>		
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 7. Type of Work Application for Permit Deepen Deepe		- - 					
PLICE DEFINITION OF WARD PROPOSED AND CHARGE OF PAIR SOURCE PROPOSED CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP Propose to: Propose to: Pull 2-3/8" tubing, run casing inspection log in 7" from surface Size of Hole Size of Casing to D with stage collar below Point Lookout and cament to surface as desired to D with stage collar below Point Lookout and cament to surface Perforate and sand water free Dakota perforations. Run 1-1/2" casing to D with stage collar below Point Lookout and cament to surface Perforate and sand water free Dakota perforations. Run 1-1/2" casing for Dakota productions N. ABOVE SIZE OF DESCRIBE PROPOSED DIROGRAM: If FORDONAL IS TO SEEPEN OF PLUS BACKS OF CEMENT PROSENT CONTROL OF PAIR CASING Water store Dakota and Point Lookout and cament to surface Perforate and sand water free Dakota and Point Lookout sand cament to surface Perforate and sand water free Dakota perforations. Run 1-1/2" Casing for Dakota productions N. ABOVE SIZE OF DESCRIBE PROPOSED DIROGRAM: If FORDONAL IS TO SEEPEN OF PLUS BACKS OF CEMENT PROSENT CONTROL OF PAIR CASING WEIGHT PROPOSED AND CEMENT PROSENT CONTROL OF PAIR CASING WEIGHT PROPOSED AND CEMENT PROPOSED							
PLICE DEFINITION OF WARD PROPOSED AND CHARGE OF PAIR SOURCE PROPOSED CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP Propose to: Propose to: Pull 2-3/8" tubing, run casing inspection log in 7" from surface Size of Hole Size of Casing to D with stage collar below Point Lookout and cament to surface as desired to D with stage collar below Point Lookout and cament to surface Perforate and sand water free Dakota perforations. Run 1-1/2" casing to D with stage collar below Point Lookout and cament to surface Perforate and sand water free Dakota perforations. Run 1-1/2" casing for Dakota productions N. ABOVE SIZE OF DESCRIBE PROPOSED DIROGRAM: If FORDONAL IS TO SEEPEN OF PLUS BACKS OF CEMENT PROSENT CONTROL OF PAIR CASING Water store Dakota and Point Lookout and cament to surface Perforate and sand water free Dakota and Point Lookout sand cament to surface Perforate and sand water free Dakota perforations. Run 1-1/2" Casing for Dakota productions N. ABOVE SIZE OF DESCRIBE PROPOSED DIROGRAM: If FORDONAL IS TO SEEPEN OF PLUS BACKS OF CEMENT PROSENT CONTROL OF PAIR CASING WEIGHT PROPOSED AND CEMENT PROSENT CONTROL OF PAIR CASING WEIGHT PROPOSED AND CEMENT PROPOSED	APPLICATIO	N FOR PERMIT TO	DRILL, DEEPEN, O	R PLUG BACK			IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
The order of the control of the cont	a. Type of Work		• /			7. Unit Agree	ment Name
News of Control Artec Otl and Ose Company Address of Operator Roy 70 Parmington, Res Mexico Roy Roy Res Roy 80 Parmington, Res	DRILL		DEEPEN X	PLUG BA	ACK 🔲 📙	8. Farm or Le	ase Name
Name of Departure Address of Company Box 70 Paradiagton, New Mexico Location of Well UNIT LETTER Box 100 Feet From the South 19, Prepased begin 20, Bottly of C.I. 10, San Juan 20, Bottly of C.I. 10, San Juan 20, Bottly of C.I. 10, San Juan 11, Prepased begin 11, Prepase		1	5	INGLE MULTI	PLE T		
Address of Company Address of Company Doc 10 Rev Marico Soc 70 Parmington, Rev Marico South Levelion of Well ONLY LETTER No. DOCATO 990 FITT FROM THE SOUTH South Levelion of Well South South Levelion of Well South South Levelion of Levelion South Levelion of Well South South Levelion of Well South South Levelion South South Levelion L		OTHER		ZONEZ	ONE CALL		· ·
Ros 570 Parmington, New Modico Location of Well Liver Storm Mark Liver Mark Liver Storm Mark Liver Mark Liver Storm Mark Liver Mark Liver Storm Mar		One Comment					4
Propose to: Propose to: P	Address of Operator	Cardinary				10. Field and	Pool, or Wildcat
Propose to: Propo	Book 570	Farmington,	New Mexico			M. 9949L	saverie-Basia
Lievedians (Sidou whether DE, RI, etc.) 21A. Kind & Status Plus. Bond 21B. Drailing Contractor 22. Approx. Date were will start 3599 DF 15A. Kind & Status Plus. Bond 21B. Drailing Contractor 22. Approx. Date were will start 3599 DF 3599		ER LOC	ATED FE	ET FROM THE South	LINE		
Elevations (Stone whether DF, BT, etc.) 21A. Kind & Status Plus. Bond 19. Proposed Logical Plants 20. Rotary of C.T. 21A. Kind & Status Plus. Bond 21B. Drilling Controctor 22. Approx. Date were will start 35990 DF 18 18 18 18 18 18 18 1			-0	10U	, ,,,,,,,,,		
Propose to: Pull 2-3/8" tubing, run casing inspection log in 7" from surface to TD squeeze open hole interval from 4680 to 4975 with approx 300 ax Squeeze open hole interval from 4680 to 4975 with approx 300 ax Squeeze open hole interval from 4680 to 4975 with approx 300 ax Squeeze open hole interval from 4680 to 4975 with approx 300 ax Squeeze open hole interval from 4680 to 4975 with approx 300 ax Squeeze possible holes in 7" casing Clean out coment to approximately 4690 and side track spen hole with knuckle joint and gas drill to 7110 Run 4-1/2" casing to TD with stage collar below Point Lookout and coment to surface Perforate and sand water frac Dekota and Point Lookout and coment to surface and sand water frac Dekota and Point Lookout ax Set Hodel D Production packer above Dakota perforations. Run 1-1/2" Casing for Dakota production ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEFER OR PLUS BACK, SIVE DATA ON PRESENT PRODUCTIVE 1 ONE ABOVE SPACE CONTROL THE BROWN PRODUCTIVE 1 ONE ABOVE SPACE OF State Use) (Original Signed) (This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 16 1966 PETROLEUM ENGINEER DIST. NO. 3 AUG 16 1966	ID 1650 FEET FROM	THE LIN	E OF SEC.	Triffirit	VIIIII	12. County	////////////////////////////////////
Propose to: Propose to: Propose to: Pull 2-3/8" tubing, run casing inspection log in 7" from surface to TD Squeeze open hole interval from 4680 to 4975 with approx 300 ax Squeeze open hole interval from 4680 to 4975 with approx 300 ax Squeeze possible holes in 7" casing Clean out casent to approximately 4690 and side track spen hole with knuckle joint and gas drill to 7110 Run 4-1/2" casing to TD with stage collar below Point Lookout and cament to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Run 1-1/2" ABOVE SPACE DESCRIBE DRODOSED DROGRAM: If PROPOSAL IS TO DEEPEN OR PLUS BACK, GIVE DATA ON PRESENT PRODUCTIVE 2 nOther above recently that the information above is true and complete to the best of my knowledge and belief. (Original Signed) (This space for Nate Use) Title District Geologist Date August 15, 1966 PETROLEUM ENGINEER DIST. NO. 3 AUG 1 6 1966						San Juan	
Propose to: Propose to: Propose to: Pull 2-3/8" tubing, run casing inspection log in 7" from surface to TD Squeeze open hole interval from 4680 to 4975 with approx 300 ax Squeeze open hole interval from 4680 to 4975 with approx 300 ax Squeeze possible holes in 7" casing Clean out casent to approximately 4690 and side track spen hole with knuckle joint and gas drill to 7110 Run 4-1/2" casing to TD with stage collar below Point Lookout and cament to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Run 1-1/2" ABOVE SPACE DESCRIBE DRODOSED DROGRAM: If PROPOSAL IS TO DEEPEN OR PLUS BACK, GIVE DATA ON PRESENT PRODUCTIVE 2 nOther above recently that the information above is true and complete to the best of my knowledge and belief. (Original Signed) (This space for Nate Use) Title District Geologist Date August 15, 1966 PETROLEUM ENGINEER DIST. NO. 3 AUG 1 6 1966	HHHHHHH	<i>HHHHHH</i>	<i>HHHHHH</i>			M	TITIIIIII
Propose to: Propose to: Propose to: Pull 2-3/8" tubing, run casing inspection log in 7" from surface to TD Squeeze open hole interval from 4680 to 4975 with approx 300 ax Squeeze open hole interval from 4680 to 4975 with approx 300 ax Squeeze possible holes in 7" casing Clean out casent to approximately 4690 and side track spen hole with knuckle joint and gas drill to 7110 Run 4-1/2" casing to TD with stage collar below Point Lookout and cament to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Run 1-1/2" ABOVE SPACE DESCRIBE DRODOSED DROGRAM: If PROPOSAL IS TO DEEPEN OR PLUS BACK, GIVE DATA ON PRESENT PRODUCTIVE 2 nOther above recently that the information above is true and complete to the best of my knowledge and belief. (Original Signed) (This space for Nate Use) Title District Geologist Date August 15, 1966 PETROLEUM ENGINEER DIST. NO. 3 AUG 1 6 1966							A Poterr of C.T.
1. Eleventions (Show whether DF, Ri, etc.) 1. Eleventions (Show white start will start blood and perform the Sacks of the Sacks			$HHHHHH$ 1 $_{16}$,, 1 10 page 2 2 - p			Zu. notary or C.1.
Propose to: Size of hole Size of casing Weight per foot Setting depth Sacks of cement Est. top			Sartua Diva Pand (2)	7110 N	essverd	22. Approx	Date Work will start
SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 6-1/4" 10.5 & 11.6 7110 300 surface Propose to: Propose to: Pull 2-3/8" tubing, run casing inspection log in 7" from surface to TD Squeeze open hole interval from 4680 to 4975 with approx 300 sx Squeeze open hole interval from 4680 to 4975 with approx 300 sx Squeeze open hole interval from 4680 to 4975 with approx 300 sx Squeeze possible holes in 7" casing Clean out cement to approximately 4690 and side track epen hole with knuckle joint and gas drill to 7110 Run 4-1/2" casing to TD with stage collar below Point Lookout and cement to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Run 1-1/2" AUG 1 6 1966 AUG 1 6 1966 (Original Signed) Tule District Geologist Date August 15, 1966 (This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 1 6 1966	1. Elevations (Show whether Di	· · ·	_			_	_
SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 6-1/4" 10.5 & 11.6 7110 300 surface Propose to: Pull 2-3/8" tubing, run casing inspection log in 7" from surface to TD Squeeze open hole interval from 4680 to 4975 with approx 300 sx Squeeze possible holes in 7" casing Clean out cement to approximately 4690 and side track epen hole with knuckle joint and gas drill to 7110 Run 4-1/2" casing to TD with stage collar below Point Lookout and cement to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Run 1-1/2" Set Model D Production packer above Dakota perforations. Run 1-1/2" AUG 1 6 1966 (Original Signed) Title District Geologist Date August 15, 1966 (This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 1 6 1966	5999 DIF						
Propose to: Pull 2=3/8" tubing, rum casing inspection log in 7" from surface to TD Squeeze open hole interval from 4680 to 4975 with approx 300 sx Squeeze possible holes in 7" casing Clean out cement to approximately 4690 and side track spen hole with knuckle joint and gas drill to 7110 Rum 4=1/2" casing to TD with stage collar below Point Lookout and cement to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Rum 1=1/2" Set Model D Production packer above Dakota perforations. Rum 1=1/2" LABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE Zunickless of tubing for Dakota production AUG 1 6 1966 (Original Signed) Title District Geologist Date August 15, 1966 PERFOVED BY ALL LAWFIELD PETROLEUM ENGINEER DIST. NO. 3 AUG 1 6 1966	· .	P	PROPOSED CASING AND	CEMENT PROGRAM			
Propose to: Pull 2-3/8" tubing, run casing inspection log in 7" from surface to TD Squeeze open hole interval from 4680 to 4975 with approx 300 sx Squeeze possible holes in 7" casing Clean out cement to approximately 4690 and side track spen hole with knuckle joint and gas drill to 7110 Run 4-1/2" casing to TD with stage collar below Point Lookout and cement to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Run 1-1/2" Lubing for Dakota production A 800VE SPACE DESCRIBE PROPOSED PROGRAM: If PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE 1 Offer PROPOSED IN CONC. STREET PROPOSED PROGRAM. IF ANY. A 800VE SPACE DESCRIBE PROPOSED PROGRAM: If PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE 1 Offer PROPOSED IN CONC. STREET PROPOSED IN Title District Geologist Date August 15, 1966 (Original Signed) (This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 1 6 1966	SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF	CEMENT	
Propose to: Pull 2-3/8" tubing, run casing inspection log in 7" from surface to TD Squeeze open hole interval from 4680 to 4975 with approx 300 sx Squeeze possible holes in 7" casing Clean out cement to approximately 4690 and side track epen hole with knuckle joint and gas drill to 7110 Run 4-1/2" casing to TD with stage collar below Point Lookout and cement to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Run 1-1/2" AUG 16 1966 NABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUS BACK, GIVE DATA ON PRESENT PRODUCTIVE 2 NOVE PROPOSED NEW PR		4-1/2"	10.5 & 11.6	7110	30	Ю	surface
Pull 2-3/8" tubing, rum chaing inspection 10g in 18th subtract of Squeeze open hole interval from 4680 to 4975 with approx 300 sx Squeeze possible holes in 7" casing Clean out cement to approximately 4690 and side track epen hole with knuckle joint and gas drill to 7110 Rum 4-1/2" casing to TD with stage collar below Point Lookout and cement to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Rum 1-1/2" AUG 1 6-1966. AUG 1 6-1966. AUG 1 6-1966 (Original Signed) Howard J. Specer (This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 1 6-1966					ł		
Pull 2-3/8" tubing, run casing inspection log in Trum surface to Squeeze open hole interval from 4680 to 4975 with approx 300 sx Squeeze possible holes in 7" casing Glean out cement to approximately 4690 and side track epen hole with knuckle joint and gas drill to 7110 Run 4-1/2" casing to TD with stage collar below Point Lookout and cement to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Run 1-1/2" AUG 1 6-1986. AUG 1 6-1986. AUG 1 6-1986. (Original Signed) Howard J. Speci. (This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 1 6-1966.				İ			
Clean out cement to approximately 4850 and side track spen into the folial to 7110 Run 4-1/2" casing to TD with stage collar below Point Lookout and cement to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Run 1-1/2" TUDING AUG 1 6-986. NABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZHOUD PROPOSED NEW PROPOSED NEW PRODUCTIVE ZHOUD PROPOSED NEW					_		
Run 1-1/2" casing to TD with stage collar below Point Lookout and cement to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Run 1-1/2" Tubing for Dakota production AUG 1 6-966. NABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZUNCHO PROPOSED NEW PROPOSED NEW PRODUCTIVE ZUNCHO PROPOSED NEW PROPOSED NEW PRODUCTIVE ZUNCHO PROPOSED NEW PROPOSED NEW PRODUCTIVE ZUNCHO PROPOSED NEW PROPO	Propose to:	ze open hole in	terval from 400	o to 4919 when	"from a	nurface t	o 150
Run 4-1/2" casing to TD with stage collar below fount location and constitution to surface Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Run 1-1/2" Tubing for Dakota production AUG 15 966 AUG 15 966 (Original Signed) Title District Geologist Title District Geologist Date August 15, 1966 AUG 16 1966	Propose to: Pull Squee	ze open hole in	terval from 400	0 to 4915 WILL	apiror .	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Perforate and sand water frac Dakota and Point Lookout zones Set Model D Production packer above Dakota perforations. Run 1-1/2" AUG 1 6 1966 NABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE Z NOTE TO DEEPEN OR PRODUCTIVE Z NOTE TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE Z NOTE TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE Z NOTE TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE Z NOTE TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE Z NOTE TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE Z NOTE TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCT	Propose to: Pull Squee Squee	ze open hole in ze possible hole out cement to	terval from 400 es in 7" casing approximately 4	690 and side tr	ack oper	hole vi	th knuckle
Set Model D Production pecker above Dakota performance tubing for Dakota production AUG 1 5 1966 NABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZINOMO PRODUCTIVE ZINOMO PRODUCTIVE ZINOMO PROPOSED NEW PRODUCTIVE ZI	Propose to: Pull Squee Squee	ze open hole in ze possible hole out cement to	terval from 400 es in 7" casing approximately 4	690 and side tr	ack oper	hole vi	th knuckle
AUG 1 5 1966 NABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE 2 NO HE PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY. hereby certify that the information above is true and complete to the best of my knowledge and belief. (Original Signed) igned Howard J. Speed (This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 1 6 1966	Propose to: Pull Squee Squee Clean	ze open hole in ze possible hole cout cement to joint and gas d ~1/2" casing to	terval from 400 es in 7" casing approximately 4 rill to 7110 TD with stage	690 and side tr	ack eper	hole wi	th knuckle
AUG 1 6 1966	Propose to: Pull Squee Squee Clean	ze open hole in ze possible hole out cement to joint and gas d ~1/2" casing to to surface	es in 7" casing approximately 4 rill to 7110 TD with stage	690 and side tre	ack eper int Look	hole wi	th knuckle
hereby certify that the information above is true and complete to the best of my knowledge and belief. (Original Signed) Howard J. Speer (This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 16 1966	Propose to: Pull Squee Squee Clean	ze open hole in ze possible hole cout cement to joint and gas de 1/2" casing to to surface wate and sand we fodel D Producti	es in 7" casing approximately 4 rill to 7110 . TD with stage ater frac Dakot on packer above	690 and side tre	ack eper int Look	hole wi	th knuckle
hereby certify that the information above is true and complete to the best of my knowledge and belief. (Original Signed) Howard J. Speer (This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 16 1966	Propose to: Pull Squee Squee Clean	ze open hole in ze possible hole cout cement to joint and gas de 1/2" casing to to surface wate and sand we fodel D Producti	es in 7" casing approximately 4 rill to 7110 . TD with stage ater frac Dakot on packer above	690 and side tre	ack eper int Look	hole wi	th knuckle
hereby certify that the information above is true and complete to the best of my knowledge and belief. (Original Signed) Howard J. Speer (This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 16 1966	Propose to: Pull Squee Squee Clean	ze open hole in ze possible hole cout cement to joint and gas de 1/2" casing to to surface wate and sand we fodel D Producti	es in 7" casing approximately 4 rill to 7110 . TD with stage ater frac Dakot on packer above	690 and side tre	ack eper int Look	hole wi	th knuckle
thereby certify that the information above is true and complete to the best of my knowledge and belief. (Original Signed) Howard J. Speer (This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 16 1966	Propose to: Pull Squee Squee Clear	ze open hole in ze possible hole cout cement to joint and gas de 1/2" casing to to surface wate and sand we fodel D Producti	es in 7" casing approximately 4 rill to 7110 . TD with stage ater frac Dakot on packer above	690 and side tre	ack eper int Look	hole wi	th knuckle
(Original Signed) Howard J. Speer (This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 1 6 1966	Propose to: Pull Squee Squee Clean Run Perfo	ze open hole in ze possible hole cout cement to joint and gas de 1/2" casing to to surface wate and sand w fodel D Producti tubing for Dako	terval from 400 es in 7" casing approximately 4 rill to 7110 TD with stage ater frac Dakot on packer above ta production	690 and side tre collar below Por a and Point Loo Dakota perfora	ack oper int Look kout zon tions.	hole wi	th knuckle cement ETELLE AUG 1 5-966
(This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 16 1966	Propose to: Pull Squee Squee Clear Run Perfc Set 1	ze open hole in ze possible hold out cement to joint and gas display casing to to surface wate and sand widel D Producti tubing for Dako	es in 7" casing approximately 4 rill to 7110 TD with stage ater frac Dakot on packer above ta production	690 and side tre collar below Por a and Point Loo Dakota perfora	ack oper int Look kout zon tions.	hole wi	th knuckle cement ETELLE AUG 1 5-966
(This space for State Use) PETROLEUM ENGINEER DIST. NO. 3 AUG 16 1966	Propose to: Pull Squee Squee Clean Run Perfc Set 1	ze open hole in ze possible hole out cement to joint and gas dul/2" casing to to surface grate and sand worded D Productional D Productional Composed Program, IF ANY.	es in 7" casing approximately 4 rill to 7110 TD with stage ater frac Dakot on packer above ta production	690 and side tre collar below Por a and Point Loo Dakota perfora	ack oper int Look kout zon tions.	hole wi	th knuckle cement ETELLE AUG 1 5-966
PETROLEUM ENGINEER DIST. NO. 3 AUG 16 1966	Propose to: Pull Squee Squee Clean Run Perfc Set I	ze open hole in ze possible hole out cement to joint and gas di wi/2" casing to to surface mate and sand wiedel D Producti tubing for Dako proposed Program, if any.	es in 7" casing approximately 4 rill to 7110 The rill to	690 and side trecollar below Porta and Point Loop Dakota perform	ack eper int Look kout zon tions.	hole wi	th knuckle cement ETELLE AUG 1 5 966 Me proposed New Produ
PPROVED BY CONTRACTOR TITLE DATE	Propose to: Pull Squee Squee Clear Run Perfo Set 1 ABOVE SPACE DESCRIBE F IVE ZONE. GIVE BLOWOUT PREVEN thereby certify that the informa (Original Signed Howard J.	ze open hole in ze possible hole in zero and gas de 1/2" casing to to surface wate and sand with tubing for Dako proposed Program: If any. Special control of the control of the program, if any.	es in 7" casing approximately 4 rill to 7110 The rill to	690 and side trecollar below Porta and Point Loop Dakota perform	ack eper int Look kout zon tions.	hole wi	th knuckle cement ETELLE AUG 1 5 966 Me proposed New Produ
PPROVED BY CONTRACTOR TITLE	Propose to: Pull Squee Squee Clear Run Perfo Set 1 A BOVE SPACE DESCRIBE FIVE ZONE. GIVE BLOWOUT PREVEN hereby certify that the informa (Original Signed Howard J.	ze open hole in ze possible hole in zero and gas de 1/2" casing to to surface wate and sand with tubing for Dako proposed Program: If any. Special control of the control of the program, if any.	es in 7" casing approximately 4 rill to 7110 TD with stage ater frac Dakot on packer above the production PROPOSAL IS TO DEEPEN Of the production of the District	690 and side tre collar below Por a and Point Loo Dakota perfora R PLUG BACK, GIVE DATA ON nowledge and belief. Geologist	ack oper int Look kout zon tions.	hole vi	th knuckle cement 2"TEVE AUG 1 5 1966
onditions of approval, If MY: 7	Propose to: Pull Squee Squee Clear Run Perfo Set 1 A BOVE SPACE DESCRIBE F IVE ZONE. GIVE BLOWOUT PREVEN thereby certify that the informa (Original Signed Howard J.	ze open hole in ze possible hole in zero and gas de 1/2" casing to to surface wate and sand with tubing for Dako proposed Program: If any. Special control of the control of the program, if any.	es in 7" casing approximately 4 rill to 7110 TD with stage ater frac Dakot on packer above the production PROPOSAL IS TO DEEPEN Of the production of the District	690 and side tre collar below Por a and Point Loo Dakota perfora R PLUG BACK, GIVE DATA ON nowledge and belief. Geologist	ack oper int Look kout zon tions.	hole wi	th knuckle cement 2"TEVE AUG 1 5 1966
	Propose to: Pull Squee Squee Clear Run Perfo Set 1 A ABOVE SPACE DESCRIBE F IVE ZONE. GIVE BLOWOUT PREVEN hereby certify that the informat (Original Signed Howard J. (This space for	reposed Program: IF ANY. The Program, IF ANY. The State Use)	es in 7" casing approximately 4 rill to 7110 TD with stage ater frac Dakot on packer above the production PROPOSAL IS TO DEEPEN Of the production of the District	690 and side tre collar below Por a and Point Loo Dakota perfora R PLUG BACK, GIVE DATA ON nowledge and belief. Geologist	ack oper int Look kout zon tions.	hole wi	th knuckle cement 2"TEVE AUG 1 5 1966

1 MA