30-045-13214

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator B	URLINGTON RESOURCE	S OIL & GAS CO.		Lease	MOORE			Well No.	1
Location									
of Well:	Unit H Sect	35 Twp.	032N	Rge.	012W	County	SAN JUAN		
	NAME OF RESERVOIR OR POOL				TYPE OF PROD.		METHOD OF PROD. PROD. MEDI		
					(Oil or Gas)	(Flo	w or Art. Lift)	(16	g. or Csg.)
Upper Completion	MESAVERDE				Gas	Flow Casi		Casing	
Lower Completion	DAKOTA				Gas Flow		Flow		Tubing
	<u> </u>	PRE-I	FLOW SHUT-IN	PRESS	URE DATA			·	
Upper	Hour, date shut-in Length of time shut-in				SI press. psig Stabilized? (Y			s or No)	
Completion	4/9/98	144 Ho	urs		406	106			
Lower Completion	4/9/98	96 Ho	urs	1010					
	 		FLOW TES	T NO.	1				
Commenced	at (hour,date)*	4/13/98	4/13/98		Zone producing (Upper or Lov		ower) LO	WER	
TIME	LAPSED TIME	PRES	SSURE		PROD. ZONE				
(hour,date)	SINCE*	Upper Completion	Lower Comple	tion	TEMP		REMARKS		
4/14/98	120 Hours	406	811				The second secon		
4/15/98	144 Hours	406	406 618						
-							PEC		/信D
	,						uu juu	1 8 3	
			,			(AND OF		1.47
Production rate	during test	. 							
Oil:	BOPD based on	Bbis. is	n	Hours		Grav.		GOR	**
						_			14.1
Gas:		MCFPD; Tested thru (Orifice or Meter):				····		
		мп-	TEST SHUT-IN	PRESS	URE DATA				
Upper Completion	Hour, date shut-in	Length of time shut-		SI press. psig			Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in	Length of time shut-	ne shut-in		ress. psig	Stabilized? (Yes or No)			

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, de	ate) * *		Zone producing (Upper or Lower):				
TIME	LAPSED TIME SINCE **	PRES	SURE	PROD. ZONE			
(hour, date)		Upper Completion	Lower Completion	TEMP.	REMARKS		
	-						
	 	 	 				
	ļ	<u> </u>					
	Į.			1			
				1			
Production rate o	luring test						
0.1	202	 .			_		
Jil:	ВОР	D based on	Bbls. in	Hours.	Grav GOR		
Gas:	 	мсі	PD: Tested thru	(Orifice or Meter)	:		
Remarks:	er alle som i er menere er er er er er er er	en e	Community Community				
				· · · · · · · · · · · · · · · · · · ·			
hereby certify t	hat the informati	on herein contain	ed is true and co	mplete <u>to the</u> best	of my knowledge		
:							
	il Conservation I		19 C	perator Sign	lington Resources		
New Mexico	in Conscivation 1	214131011	В	· Pela	# Han		
	Johnny	Relience			tim associate		
Зу	•		T T	ide <u>Spiva</u>	tim invocate		
Title	Deputy Oil 8	Gas Inspecto	f I	Date	7/98		
							

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well, Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-manute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).