API#

30-045-20464

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT This form is not to be used for reporting packer leakage tests in Southeast New Mexico

OIL CONSERVATION DIVISION

Page I Revised 10/01/78

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

| Operator E | BURLINGTON RESOURCES OIL & GAS CO. | | | | | | Lease HUBBARD | | | | Well No. 4 | |
|---------------------|---|---------------|-----------------------------|------------------------|--------------------|-------------------|-------------------------------|-------------------------------------|----------------------------|------------------|---------------|---------------|
| Location of Well: | Unit | М | Sect | 15 | Т | 02011 | | | | | | |
| | | | | | Twp. DIR OR POO | 032N | Rge. | 012W | County | SAN JUAN | | |
| | | *** | TWIE OI | RESERVO | JIK OK POO | L | T | YPE OF PROD. | | OD OF PROD. | PRO | DD. MEDIUM |
| Upper | + | | | | | | | (Oil or Gas) | (Flov | w or Art. Lift) | (1 | (bg. or Csg.) |
| Completion | MESAVERDE | | | | | | | Gas | Flow Tubing | | Tubing | |
| Lower Completion | DAKOTA | | | | | | | Gas | Flow | | | Tubing |
| - | | | | | PRE- | FLOW SHUT-I | V PRESS | URE DATA | | | | |
| Upper | late shut-ii | 1 | Length | of time shut- | | | | | or M-1 | | | |
| Completion | 4/24/98 | | | 72 Hours | | | 556 | | Stabilized? (Yes or No) | | | |
| Lower Completion | 4/24/98 | | | 120 Hours | | | | | | | | |
| | 1 | | | | 120 110 | | CT NO | 496 | | | | |
| Commenced | at (hour da | ate)* | | - · | 4/07/00 | FLOW TE | ST NO. | | | | | |
| TIME | LAPSED TIME | | | 4/27/98 | | | | Zone producing (Upper or Lower) UPF | | | | |
| (hour,date) | SINCE* | | PRESSURE | | | | PROD. ZONE | | | | | |
| (nour,uate) Since | | | Upper Completion Lower Comp | | | letion | ТЕМР | | REMARKS | | | |
| 4/28/98 | 96 Hours | | | 2 | 183 | 555 | | | Opened upper zone for flow | | | |
| 4/29/98 | 120 Hours | | 281 608 | | | | All is ok. | | | | | |
| | | | | | | | | | All is of | | GA. | MEA |
| | | | | | | | | | | | | |
| roduction rate | during test | - | | <u></u> | | | | | | £ | • | Sally 1 |
| Dil: | В | OPD base | ed on _ | | Bbls. in | | Hours. | | Grav. | | GOR | |
| Gas: | | | | MCFPD; T | ested thru (O | rifice or Meter): | | | | | | |
| | | | | | MID-T | EST SHUT-IN | PRESSU | RE DATA | | | | |
| Upper Completion | Hour, date shut-in Length of time shut-in | | | | | | SI press. psig Stabilized? (Y | | | or No) | | |
| Lower Completion | Hour, date shut-in | | | Length of time shut-in | | | SI press. psig Stabilized? (| | | Stabilized? (Yes | or No) | |

(Continue on reverse side)

| mmenced at fhour, da | 11e) * * | | Zone producing (Upper e | or Lowert | | | |
|----------------------|--|--|-------------------------|--------------------|-------------------|--|--|
| TIME (hour, date) | LAPSED TIME | PRESSURE | | PROD. ZONE | REMARKS | | |
| | SINCE ** | Upper Completion | Lower Completion | TEMP. | | | |
| | | | | | | | |
| | ļ | | | | | | |
| | | | | ļ | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| Production rate (| during test | | | | | | |
| Oil: | BOI | PD based on | Bbls. in | Hours | Grav GOR | | |
| | | | | | | | |
| | | | | | | | |
| Remarks: | and the second s | emilian i Albert ergelangsbereit (1977) (1977) sejer erdei | | | | | |
| | | | | | | | |
| 1 | | | | | | | |
| I hereby certify | that the informa | tion herein contai | ned is true and co | mplete to the best | of my knowledge | | |
| i | | | | - Zan | lington Resources | | |
| Approved | <u> </u> | 1988 | 19 (| perator Sou | may recommended | | |
| New Mexico (| Oil Conservation | Division | 1 | y Relai | # Han | | |
| | | | | | Im maiate | | |

NORTHWEST NEW MEDICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrutbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Deputy Oil & Gas Inspection

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seen days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1, Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut in while the zone which was previously shut in is produced.
- 7. Pressures for gas-zone term must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at furteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period, 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing , temperatures (gas zones only) and gravity and GOR (oil zones only).