

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 4282

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

LA PLATA

9. WELL NO.

2 (F-30)

10. FIELD AND POOL, OR WILDCAT

Undesignated Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 30, T-32N, R-13W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6477' GR

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒
☒

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-14-76 PBTD 3246'. Perforated with one jet shot at each of the following depths: 3093', 3092', 3091', 3090', 3089', 3088', 3067', 3066', 3065', 3050', 3049', 3048', 3047', 3046', 3045', 3044', 3043', 3042', 3041', 2999', 2998', 2997'. Set Baker Model B tool across each perforation and pumped 100 gallons acid. Breakdown pressures varying from 400# to 3500#. Experienced some communication between perforations. Displaced all acid into perforations following individual breakdown of perforations. Commenced swabbing back acid water.

4-25-76 Premixed 3,200 barrels of water with 1% potassium chloride and 3 gallons per 1,000 gallons F-75 surfactant. Sand-water fraced using 24,000# 20/40 sand and 69,000# 10/20 sand. Mixed J-266 gelling agent at 50# per 1,000 gallons treated water. Average injection rate 32 BPM, average treating pressure 2400#. Inst. SDP 1250#, 1-min. SIP 1200#.

4-26-76 Well on vacuum.

18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

Vice-President

DATE

4-27-76

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED
APR 30 1976
U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.