

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF-078312

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Culpepper Martin

9. WELL NO.

#5-A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 22, T32N, R12W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

1. OIL ☐ GAS ☒ OTHER
WELL WELL

2. NAME OF OPERATOR

Aztec Oil & Gas Company

3. ADDRESS OF OPERATOR

P. O. Drawer 570, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1650' FNL & 1610' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6113' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Casing report

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-7-77 Ran 72 joints of 7", 20#, K-55, 8rd casing. Total 2821.25', shoe set at 2802', insert float valve set at 2764.88'. Cemented with 108 sacks 65/35 Poz with 12% gel followed with 70 sacks Class "B" with 2% CaCl. Plug down at 2:20 AM.

3-11-77 Ran 71 joints of 4-1/2", 9.5#, k-55, 8rd casing. Total 2456.79', shoe set at 5130, float collar set at 5129', liner hanger set at 2658.61'. Cemented with 20 barrels gel water and 313 sacks 50/50 Poz A, Class "B" with 2% gel, 6.25# fine gilsonite per sack, 1/4# gel flake per sack and 0.6% Halad 9. Plug down at 2:00 AM.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Production Manager

DATE May 12, 1977

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: