

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
EL PASO NATURAL GAS COMPANY

3. ADDRESS OF OPERATOR
Box 990, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1850'N, 1500'W
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other)

SUBSEQUENT REPORT OF:

☒
☒
☐
☐
☐
☐
☐
☐

5. LEASE
SF 078147

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Moore

9. WELL NO.
7A

10. FIELD OR WILDCAT NAME
Blanco M.V.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 25, T-32-N, R-12-W
N.M.P.M.

12. COUNTY OR PARISH
San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6524 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-12-78 T.D. 3452'. Ran 107 joints 7", 20#, KS intermediate casing, 3440' set at 3452'. Cemented with 393 cu. ft. cement. W.O.C. 12 hours, held 1200#/30 minutes. Top of cement at 1300'.

6-15-78 T.D. 5792'. Ran 78 joints 4 1/2", 10.5#, KS casing liner, 2512' set 3281-5792'. Float collar set at 5776'. Cemented with 438 cu. ft. cement. WOC 18 hours.

7-7-78 P.B.T.D. 5776'. Tested casing to 3500#, O.K. Perfed 5173, 5295, 5321, 5328, 5335, 5367, 5375, 5381, 5390, 5397, 5400, 5415, 5424, 5431, 5438, 5491, 5506, 5525, 5544, 5553, 5582, 5605, 5671, 5704' w/1 SPZ. Fraced with 83,000# 20/40 sand and 167,496 gallons water. Flushed with 7392 gallons water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____


18. I hereby certify that the foregoing is true and correct

SIGNED D. P. Guisco TITLE Drilling Clerk DATE 8-3-78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



GEOLOGICAL SURVEY
WASHINGTON, D.C.