

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

97 FEB 10 PM 1:33

1. Type of Well
GAS

070 FARMINGTON, NM

5. Lease Number
SF-078118

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

820' FNL, 810' FWL, Sec. 31, T-32-N, R-11-W, NMPM

D

8. Well Name & Number

Lawson #4

9. API Well No.

30-045-23407

10. Field and Pool

Glades Fruitland Sd/
Blanco Pictured Cliffs

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

1-2-97 MIRU. ND WH. NU BOP. TIH. Plug #1: pump 50 sx Class "B" cmt down Pictured Cliffs tbg @ 1303-3118'. Plug #2: pump 96 sx Class "B" cmt inside Fruitland Sand tbg @ 0-2898'. WOC. SDON.

1-3-97 PT Fruitland Sand tbg & Pictured Cliffs tbg to 500 psi, OK. TIH, tag TOC in Fruitland Sand tbg @ 124'. TOOH. TIH, tag TOC in Pictured Cliffs tbg @ 1477'. Perf 2 sqz holes @ 912'. TOOH. Establish injection. Plug #3: pump 55 sx Class "B" neat cmt outside Pictured Cliffs tbg @ 812-912'. Pump 10 sx Class "B" neat cmt inside Pictured Cliffs tbg @ 549-1477'. WOC. TIH to 1000', did not tag TOC. Establish injection into perfs @ 912'. Plug #4: Pump 65 sx Class "B" neat cmt outside Pictured Cliffs tbg. Pump 10 sx Class "B" neat cmt inside tbg to 549'. WOC. SD for weekend.

1-6-97 TIH, tag TOC @ 631' in Pictured Cliffs tbg. Perf 2 sqz holes in Pictured Cliffs tbg @ 195'. TOOH. Establish circ down csg & out bradenhead w/3 bbl wtr. Plug #5: pump 78 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Fill Fruitland Sand tbg w/2 sx Class "B" neat cmt. Install dry hole marker w/8 sx Class "B" neat cmt. RD. Rig released. Well plugged and abandoned 1-6-97.

14. I hereby certify that the foregoing is true and correct.

Signed Doane W. Spencer Title Regulatory Administrator Date 2/6/97

(This space for Federal or State Office use)

APPROVED BY Doane W. Spencer Title

CONDITION OF APPROVAL, if any:

RECEIVED
FEB 14 1997

FEB 12 1997

OIL CON. DIV.
DIST. 3

NMOCD