

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ well ☐ other ☐  
2. NAME OF OPERATOR  
AMOCO PRODUCTION COMPANY  
3. ADDRESS OF OPERATOR  
501 Airport Drive Farmington, NM 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1150' FSL x 850' FWL, Section 25,  
AT SURFACE: T32N, R14W  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  
TEST WATER SHUT-OFF ☐ ☐  
FRACTURE TREAT ☐ ☐  
SHOOT OR ACIDIZE ☐ ☐  
REPAIR WELL ☐ ☐  
PULL OR ALTER CASING ☐ ☐  
MULTIPLE COMPLETE ☐ ☐  
CHANGE ZONES ☐ ☐  
ABANDON\* ☐ ☐  
(other) Spud & Set Casing

5. LEASE I-22-IND-619  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Ute Mountain Tribe  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Ute Indians "A"  
9. WELL NO. 14  
10. FIELD OR WILDCAT NAME  
Ute Dome Dakota  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SW/4 SW/4 Section 25, T32N, R14W  
12. COUNTY OR PARISH San Juan  
13. STATE NM  
14. API NO. 30-045-23500  
15. ELEVATIONS (SHOW DE, KDB, AND WD)  
6858' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 12-1/4" hole on 6/15/79. Drilled to 330'. Set 8-5/8", 24# casing at 330' with 225 sx Class "B" Neat, 2% CaCl<sub>2</sub> cement. Circulated out 8 sx good cement.

Drilled 7-7/8" hole from 330' to TD. Set 4-1/2", 10.5# casing at 3445' with 610 sx Class "B", 2% CaCl<sub>2</sub> Neat cement. Tailed in with 110 sx Class "B" Neat, 2% CaCl<sub>2</sub> cement.

Drilling rig released on 6/23/79.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED J. E. Luohada TITLE Dist. Adm. Supvr. DATE 7/9/79

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: