(4) 3r

# Hallwood Petroleum, Inc.

4582 South Ulster Street Parkway · Stanford Place III · Suite 1700 · Post Office Box 378111 Denver, Colorado 80237 · (303) 850-7373

#### **CERTIFIED MAIL NO. 212 222 132**

October 29, 1997

Mr. David Catanach,
Hearing Examiner
State of New Mexico
Oil Conservation Division
2040 South Pacheco
Santa Fe, New Mexico 87505

RE:

Approval to Accept Additional Water

Cardon Com #1 (SWD)

Unit A – Section 27-T32N-R13W San Juan County, New Mexico Administrative Order SWD-632

Dear Mr. Catanach:

Hallwood Petroleum, Inc. is the Operator of the Cardon Com #1 (SWD) well in San Juan County, New Mexico. This well was approved for underground disposal of produced water by Administrative Order SWD-632 on July 9, 1996. The well currently disposes of produced Fruitland Basin Coal water from offset Hallwood Petroleum, Inc. wells into the Entrada formation in the Cardon Com #1 (SWD) at 7780'-7910' (130' interval of high quality 15% porosity sandstone).

As a result of increased drilling and production activity in the area surrounding Hallwood's wells and acreage, three (3) operators have contacted Hallwood with a request to take (and dispose of) produced Fruitland Basin Coal water from their wells.

Hallwood contacted Mr. Ernie Busch in the Aztec, New Mexico office and discussed the possibility of accepting and disposing of outside operated water into the Cardon Com #1 (SWD). We wanted to know whether or not this would classify as a "commercial disposal operation" or be in violation of our approved disposal permit. Mr. Busch said that it would not be a problem for the OCD or UIC if we disposed of outside operated similar waters. However, he suggested that we contact you and inform you of this situation; thus, this is the purpose of this letter.

Mr. David Catanach State of New Mexico Oil Conservation Division October 29, 1997 Page 2

Attached is a Form C-103 Sundry Notice with a list of the five (5) outside operated wells for which we are currently taking water. Water analyses are also included for three (3) of the wells. Hallwood Petroleum, Inc. foresees no problem in accepting this similar type of water for disposal into the Cardon Com #1 (SWD). By disposing of this water, it will enable the other companies to adequately production test their wells without the much higher disposal cost involved with transporting the water 15-20 miles away. Also, the Cardon Com #1 (SWD) is currently disposing of 500-600 BWPD at 578 psig which is significantly below the approved maximum pressure of 1528 psig. Thus, additional water volumes should not present any problems as we are "under-utilizing" the well.

Please contact me at (303) 850-6303 should you have any questions or require additional information.

Sincerely,

HALLWOOD PETROLEUM, INC.

Kevin E. O'Connell

Drilling and Production Manager

KEO/jey

Attachments

cc:

Eva Kardas Nonya Durham

OCD – District III Ernie Busch 1000 Rio Brazos Road Aztec, NM 87410

KEO97.076

Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-10? Revised 1-1-89

### OIL CONSERVATION DIVISION

DISTRICT I P. O. Box 1980, Hobbs, NM 88240 DISTRICT II	Box 1980, Hobbs, NM 88240 Santa Fe New Mexico 87505		WELL API NO. 30-045-24392
811 S. First St., Artesia, NM 88210-2834  DISTRICT III  1000 Rio Brazos Rd, Aztec, NM 87410	5. Indicate Type of Lease  STATE FEE  FEE		
			6. State Oil & Gas Lease No. N/A
(DO NOT USE THIS FORM FOR PROPOSALS DIFFERENT RESERVOIR. US	ND REPORTS ON WELS TO DRILL OR TO DEEPEN ( SE "APPLICATION FOR PER R SUCH PROPOSALS.)	OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
1. Type of Well: OIL GAS WELL	OTHER SWD Well		Cardon Com
Name of Operator     Hallwood Petroleum, Inc.			8. Well No.
3. Address of Operator P. O. Box 378111, Denver 4. Well Location	, CO 80237		9. Pool name or Wildcat SWD (Entrada)
Unit LetterA:1120			1050 Feet From The East Line
Section 27 Township  11. Check Appropria	10. Elevation (Show wheth	5909' KB 58	99' GL
NOTICE OF INTENTION	te Box to Indicate Na	1	SEQUENT REPORT OF:
	JG AND ABANDON L	REMEDIAL WORK COMMENCE DRILLING	OPNS. D PLUG AND ABANDONMENT
PULL OR ALTER CASING  OTHER:Approval to accept addition	al water	CASING TEST AND CE	EMENT JOB
12. Describe Proposed or Completed Operations (Composed) SEE RULE 1103.  Hallwood Petroleum, Inc. requests approximate Cardon Com #1 (SWD):  1. Merrion Oil & Gas Corp., Powel: 2. Merrion Oil & Gas Corp., Havast Gas Corp., Havast Gas Corp., Taurus Exploration, Inc., Culpeter Taurus Exploration, Inc., Culpeter Composed Composed Gas Corp.	roval to accept produce  1 #1, SE NE Sec. 22-T3  41, SE SE Sec. 28-T32  epper Martin #9, Sec.	ed Fruitland Coal wa 2N-R13W, San Juan C 2N-R13W, San Juan C N-R13W, San Juan Co 6-T31N-R12W, San Ju	ater from the following wells into the O., NM O., NM ., NM an Co., NM
			lumes from the five wells are estimated
I hereby certify that the information above is true and SIGNATURE Ann G. Complete	Defftitle_	-	oduction Mgr_DATE_10/29/97
TYPE OR PRINT NAME Ke√in E. O (This space for State Use)	'Connell		TELEPHONE NO. 303-850-6303
APPROVED BY	TITLE		DATE
CONDITIONS OF APPROVAL IF ANY			



#### **MERRION OIL & GAS CORPORATION**

610 REILLY AVENUE FARMINGTON, NEW MEXICO 87401

### FAX COVER SHEET

DATE:

September 9, 1997

TIME:

8:34 AM

TO:

Hallwood Petroleum

PHONE:

303.850.6303

Kevin O'Connel

FAX:

303.850.6290

FROM:

Steven Dunn

PHONE:

505.327.9801

Merrion Oil & Gas

FAX:

505.326.5900

RE:

WATER DISPOSAL... POWELL 1, HAVASU 1

CC:

Well Files

Number of pages including cover sheet: 2

### Message

Merrion hereby requests that Hallwood dispose of produced water from the following Basin Fruitland Coal gas wells:

#### 1. Powell No. 1

2050' fnl & 790' fel (se ne) Sec 22, T32N, R13 W, NMPM San Juan County, New Mexico

#### 2. Havasu No. 1

790' fsl & 790' fel (se se) Sec 22, T32N, R13W, NMPM San Juan County, New Mexico

Both wells are producing water from the Main Fruitland Coal and an analysis is attached for the Powell No. 1 well. Merrion's Operator OGRID number is 14634; no well OGRID numbers have been assigned to the producing wells at this time.

Estimated water volumes are up to 300 bbl per day for the two wells combined.

Produced water would be trucked to Hallwood's facilities over existing roads.

If further is required, please give me a call.

### POWELL NO. 1 (	FIELD	WATER	RS TO D	EPOSI	CALC	<u>IUM CA</u>	RBONAT	E	
COMMATION:   FRUITLAND   Remarks   Report Date:   8/27/97   Report Date:   Report Date:   8/27/97   Report Date:   Report Da				<u> </u>	-11				
Report Date:   9/27/97	NELL NAME:	POWE	LL NO.	<u>1 (i</u>	NEIL NO	1 ON	C-103)	.,	
CONCENTRATION:   Na + K=   706   ppm/mg/l   30,71   meq/liter   Na + K=   706   ppm/mg/l   0.50   meq/liter   Na + K=   706   ppm/mg/l   0.00   meq/liter   Na + K=   706   ppm/mg/l   10   10   10   10   10   10   10   1	ORMATION:	FRUITLAN	D	Remarks:					
Na + K= 706 ppm/mg/l 30.71 meq/liter 2	Report Date:	8/27/97							
Ca =   18   ppm/mg/    0.90   meq/liter   Ca	CONCENTRATION:						LOGARITHMIC	PROFILE	
Column	la + K=	706	ppm/mg/l	30.71	meq/liter	No more		CI	
Mg =   7   ppm/mg/1   0.58   meq/liter   G   1.000   meq/liter   Mg	Ca =	18	ppm/mg/l	0.90	meq/liter	E::			
C  =   355   ppm/mg/  10.01   meq/liter   Mg	Mg =			0.58	meq/liter	Cs 🖺		нсоз	
1	e =			0.00	meq/liter				
DOC	<b>a</b> =	355	ppm/mg/l	10,01	meq/liter	- (mail 1)		and a record of the second	
Description   Demminary   De	HCO3 =	1,354	ppm/mg/l	22.21	meq/liter	Fa Fig	erit mili Sila di Sult mili Sila di		
DS							eile.		
TOS				7			10 1	10	
Spec. Grav.   1.0000   TEMP (°F) TEMP (°C)   K   Scale Index						10.00	000	1,00010,000	
Spec. Grav. 1.0000 TEMP (°F) TEMP (°C) K Scale Index  OH FACTOR = 8.27 60 15.6 2.941 0.368 *  ICa = 3.321 80 26.7 2.719 0.590 *  OAIK = 1.640 100 37.8 2.457 0.852 *  Total Hardness = 73.8 mg/l 120 48.9 2.164 1.145 *  Ica = 1.640 100 1.844 1.466 *  Ica = 1.640 1.844 1.466 1.46			···					10,000	
## FACTOR = 8.27   60   15.6   2.941   0.368   ▼   ## OCa = 3.321   80   26.7   2.719   0.590   ▼   ## OAIK = 1.640   100   37.8   2.457   0.852   ▼   ## OTAIL HARDNESS = 73.8   mg/l   120   48.9   2.164   1.145   ▼   ## 4.32   grains/gal   140   60.0   1.844   1.466   ▼   ## Resistivity = 4.50   ohm-m	·								
## FACTOR = 8.27   60   15.6   2.941   0.368   ▼   ## OCa = 3.321   80   26.7   2.719   0.590   ▼   ## OAIK = 1.640   100   37.8   2.457   0.852   ▼   ## OTAIL HARDNESS = 73.8   mg/l   120   48.9   2.164   1.145   ▼   ## 4.32   grains/gal   140   60.0   1.844   1.466   ▼   ## Resistivity = 4.50   ohm-m	Spec. Grav.	1,0000		TEMP (°F)	TEMP (°C)	K	Scale Index		
SCa =   3.321			<del> </del>			2.941	0.368	*	
SAIK =   1.640   100   37.8   2.457   0.852   *						2.719	0.590	*	
Total Hardness =   73.8   mg/l   120   48.9   2.164   1.145				100		2.457			
A 32   grains/gal   140   60.0   1.844   1.466   T									
160   71.1   1.499   1.810   *	rotal Hardriess -								
Resistivity = 4.50 ohm-m @ 74°F  2.00 1.80 1.60 1.40 1.20 1.00 0.80 0.40 0.20 0.00 60 80 100 120 140 160  TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved  All Rights Reserved		4.52	granisigui				1	*	
2.00 1.80 1.60 1.40 0.80 0.60 0.40 0.20 0.00 60 80 100 120 140 160 TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved All Rights Reserved	Pecietivity -	4.50	ohm-m @		71.1.	1.100	1,5,5		
1.80 1.60 1.40 1.20 1.20 1.00 0.80 0.40 0.20 0.00 60 80 100 120 140 160  TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved  All Rights Reserved	resistivity -	4.50	i i	177.			ł		
1.80 1.60 1.40 1.20 1.20 0.80 0.60 0.40 0.20 0.00 60 80 100 120 140 160  TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved All Rights Reserved									
1.60 1.40 1.20 1.00 0.80 0.60 0.40 0.20 0.00 60 80 100 120 140 160  TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved	A 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	ŧ		787 1 X		1	-		
1.40 1.20 1.00 0.80 0.60 0.40 0.20 0.00 60 80 100 120 140 160  TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved	1.0000000000000000000000000000000000000					T			
0.40 0.20 0.00 60 80 100 120 140 160  TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved  All Rights Reserved					•				
0.40 0.20 0.00 60 80 100 120 140 160  TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved  All Rights Reserved	1.40						•		<del> </del>
0.40 0.20 0.00 60 80 100 120 140 160  TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved  All Rights Reserved	¥ 1.20 ]								
0.40 0.20 0.00 60 80 100 120 140 160  TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved  All Rights Reserved	1.00								<b></b>
0.40 0.20 0.00 60 80 100 120 140 160  TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved  All Rights Reserved	ີ່ 0.60	•							<del> </del>
0.00 60 80 100 120 140 160  TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved  A POSITIVE INDEX INDICATES SCALE FORMATION. A NEGATIVE	~~ (0.0000000000000000000000000000000000								-
60 80 100 120 140 160  TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved  All Rights Reserved	0.20	- <b></b>							
TEMP - °F  (C)Copyright 1990 by Douglas M. Boone All Rights Reserved	0.00	<del>-</del>							-
(C)Copyright 1990 by Douglas M. Boone All Rights Reserved	60	80	100	120	140	160	<del></del>	ļ- <del></del>	
(C)Copyright 1990 by Douglas M. Boone All Rights Reserved			TEMP	•=					
A POSITIVE INDEX INDICATES SCALE FORMATION. A NEGATIVE All Rights Reserved			IEMP	· - r			<sub></sub>	CVCoouricht 1999	
A POSITIVE INDEX INDICATES SCALE FORMATION. A NEGATIVE All Rights Reserved									<u> </u>
NDEX INDICATES CORROSION.   Vacsion 1.1.				RMATION.	A NEGATIV	/E	Α	II Rights Reserved	
	NDEX INDICATES (	CORROSION.						ecsion 1.1.	<u> </u>
		1	1	1	1	I .	1	1	1

TEL NO: 303 259 1418

14,197 05:50AM\_

10/10/97 12:18 FAX 503 327 4982


COLEMAN OIL GAS

(Z) (U)

From: WEPC (505) 327-4892

Sep. 23. 1997 29: 45 AM

P81



## Water Analysis Report

To:	Walsh Engineering	Date:	9/20/97
Submitted by:	Hallibuston Energy Services	Date Race	9/18/97
Affention;	Paul Thompson	Report #:	
Well Name:	Steward Com #1	Formstion	Fruitlend Cont
	( Well # 3 ON C-103)		

Specific Gravity	1.002
РЩ	7.17
Resistivity	@ 70° F
Iron (FE)	12.20 Mg/L
Potasium (K)	250.00 Mg/L
Sodium (Na)	. RS5.R Mg/L
Calcium (Ca)	. 41 Mg/L
Magnesium (Mg)	23 Mg/L
Chlorides (Cl)	1477 Mg/L
Sulfates (SO4)	300 Mg/L
Carbonates (CO3)	0 Mg/L
Bicarbonates (HCO3)	102 Mg/L
Total Dissolved Solids	3092 Mg/L

Respectfully: Colu Robinson

Title: Field QC

Location: Farmington, NM

TEL NO: 303 259 1418 SEP 30 437 185: 446 FAX NO. 505 326 6112


SEP-26-97 FRI 08:35 AM



San Juan Office 2198 Bloomfield Highway Farmington, New Moxico 87401 (505)325-6800, FAX (505)326-6112

٠O:	*Hallwood Petroleum (970)259-1418	 		
	• • • • • • • • • • • • • • • • • • •			
ATTN:	*Jim Boneventura	 		
FROM:	*Gary <b>B</b> rink	 ·	· 	
DATE:	*September 26, 1997		<u> </u>	
OVERN	MESSAGE:			

Form TA-205-252-9562 Rev. 9-92



## Water Analysis Report

To:	TAURUS ENPLORATIONAVALSII	Date:	9/24/97
Summitted by:	Hallibucton Energy Services	Date Rec:	9/24/97
Ailention;		Report #:	WF-97-0174
Well Name:	CULPEPPER MARTIN 9 OF OUNDER	Formation:	FRUITLAND COAL
Well Name;			
	Sec 6-T3IN-RIZW (Well No 4- ON C-103)		
Specific Gravity	y	1.000	!
рН		7.83	
Resistivity		1.60	@ 70a F
Iron (FE)		· 1	Mg/L
Potasium (K)		0	Mg/I.
Sodium (Na)		2065	Mg/1.
Calcium (Ca)	÷	49	Mg/l.
Magnesium (M	( <b>5)</b>	167	Mg/1.
Chlorides (Cl)		499	Mg/L
Sulfates (SO4)		Ů	Mg/L
Carbonates (C	03)	0	Mg/L
Bicarbonates (		5612	Mg/1.
Total Dissolver	1 Solids	8393	Mg/1.

Respectfully:	Teresa White
Title:	Lah Tech
Location:	Furndagton, NM

Total Dissolved Solids

# MONTHLY INJECTION DATA Cardon Com #1, San Juan County, New Mexico

Month	Injection	Days [	Average	Cumulative	Average
Year	Bbls	Injected	Bw/D	] Inj. Bbls	Pressure
9/96	22300	10	2230	22300	233
10/96	21464	27	795	43764	320
11/96	27391	30	913	71155	558
12/96	26133	31	843	97288	626
TOTAL 96	97288	98	1195	97288	434
========	= ==========	=======================================	========		- ========
1/97	20149	31	650	117437	556
2/97	17569	28	627	135006	556
3/97	18517	30	617	153523	583
4/97	14069	21	670	167592	471
5/97	13950	31	450	181542	481
6/97	12941	30	431	194483	450
7/97	12894	31	416	207377	484
8/97	18044	31	582	225421	543
9/97	20956	30	699	246377	578
10/97					
11/97					
12/97					
TOTAL 97	149089	263	571	246377	522