

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Southland Royalty Company 3. Address of Operator P.O. Drawer 570, Farmington, New Mexico 87401 4. Location of Well UNIT LETTER <u>A</u> <u>975</u> FEET FROM THE <u>north</u> LINE AND <u>790</u> FEET FROM THE <u>east</u> LINE, SECTION <u>29</u> TOWNSHIP <u>32N</u> RANGE <u>12W</u> NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 5955' GR	7. Unit Agreement Name 8. Farm or Lease Name Culpepper Martin 9. Well No. 19 10. Field and Pool, or Wildcat Wildcat Pictured Cliffs 12. County San Juan
---	---

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	Casing Report <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-3-81 Ran 84 joints (2527.06') of 2-7/8", 6.5#, J-55 casing set at 2539'.
Cemented with 700 sacks of Class "B" 50/50 Poz with 1/4# gel flake per sack and
6% gel, followed with 50 sacks of Class "B" Neat with 2% CaCl₂.
Plug down at 3:30 P.M. 1-3-81. Top of cement at 500'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ester Hernandez TITLE Drilling Clerk DATE Jan. 5, 1981

Original Signed by FRANK T. CHAVEZ

SUPERVISOR DISTRICT # 3

APPROVED BY _____ TITLE _____ DATE JAN 7 1981

CONDITIONS OF APPROVAL, IF ANY: