

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
Box 3249, Englewood, Co 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1710' FNL 910' FEL "H"
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

SF - 078146

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Newberry A

9. WELL NO.

4 E

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 34 T 32N R12W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

-6233' ground

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/2/81 WOC. NUWH. Pressure test BOP to 1500 PSI. TIH. Tag DV @ 3889'. Pressure test pipe rams to 1500 PSI. Drill cmt and DV. Clean out to float collar @ 4911'. Pressure test csg to 3000 PSI 1/2 hr OK. Resume drilling.
4/3/81 Drill to TD of 7490'.
4/5/81 Blow hole. TOOH. Log w/ Welex. TIH. RU and run 11 jts (509') 4 1/2" 11.6# and 50 jts (2160') 4 1/2" 10.5# csg. Cmt w/ 350 sx 65/35sx POZ w/ 6% gel and 6% NFL-2, Tail in w/ 150sx Class B. Csg set @ 7489' float collar @ 7440' and top of liner @ 4811'KB. Reverse out 5bbbls cmt. Circ cmt to top of csg. Release rig 4/5/81.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carley Watkins TITLE Asst. Div. Adm. Mgr. DATE April 16, 1981

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL IF ANY:
ACCEPTED FOR RECORD

APR 23 1981

*See Instructions on Reverse Side

FARMINGTON DISTRICT

BY Carley Watkins