	Form Approved.	
:	Budget Bureau No. 42-R142	4

DEPARTMENT OF THE INTERIOR	5. LEASE NM-010989
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas	Fields 9. WELL NO.
2. NAME OF OPERATOR	1E
Tenneco Oil Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR P. O. Box 3249, Englewood, CO 80155	Basin Dakota
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.)	Sec. 29, T32N R11W
AT SURFACE: 1525' FSL 970' FEL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	San Juan NM
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	24. AFT NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6336' gr.
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	VED
	Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	1982
ABANDON*	
(other) Bradenhead Squeeze U. S. GEOLOGICA FARMINGTON,	NL SURVEY
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent	e all pertinent details, and give pertinent dates,
3/30/82 - Pld hoist and pmp truck to location v	24
into bradenhead @ 1 BPM and 900 psi. Killed we	ell w/1% KCL wtr. Removed WH and
installed BOP.	
3/31/82 - Killed well w/1% KCL wtr. Tagged PBT	${\tt FD}$ @ 7665'. ${\tt POOH}$ w/tbg and ${\tt SN}$. Ran
WL RBP and set @ 3000'. PT to 1000 psi. Test	good. Ran CBL over Ojo Alamo
formation w/1000 psi on csg. TOC @ 2220'. No 4/1/82 - Dumped 2 sxs sd on top of RBP. PT to	omt over Ojo Alamo.
csg @ 1300-04' w/4" csg gun w/l JSPF. RIH w/th	og and full bore pkr to 1155' Set
pkr and established circ to surface thru brader	nhead. Cemented 7" csg to surface
w/190 sxs Class B neat followed w/110 sxs Class	B neat w/2% CACL2. Displaced cmt
w/7 BW.	
	·
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED Denise Wilson Wilson Ana	Alyst DATE 4/6/82
(This space for Federal or State office	ce web)
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	ACCEPTED FOR RECORD
	- 0.0 1000
*See Instructions in Reverse \$	APR 09 1982
See Instructions on Reverse \$	

FARMINGTON DISTRICT