

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Southland Royalty Company		8. Farm or Lease Name Day State
3. Address of Operator P.O. Drawer 570, Farmington, New Mexico 87401		9. Well No. #2-E
4. Location of Well UNIT LETTER <u>H</u> , <u>1930</u> FEET FROM THE <u>North</u> LINE AND <u>1230'</u> FEET FROM THE <u>East</u> LINE, SECTION <u>32</u> TOWNSHIP <u>32 North</u> RANGE <u>11 West</u> NMPM.		10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 6277' GL		12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Spud & Casing Report</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-05-81 Spudded 12-1/4" surface hole at 10:00 P.M. 5-5-81 and drilled to total depth of 235'. Ran 6 joints 214.80' of 9-5/8", 32.30#, H-40 casing set at 226'. Cemented with 200 sacks of Class "B" with 1/4# gel flake per sack and 3% CaCl₂. Plug down at 6:00 A.M. 5-6-81. Cement circulated to surface.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Esther L. Chavez TITLE Drilling Clerk DATE May 6, 1981

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE MAY 8 1981

CONDITIONS OF APPROVAL, IF ANY: