

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
PO Box 4289, Farmington, NM 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1560'S, 1660'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☒
☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF 078147
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Moore
9. WELL NO.
9
10. FIELD OR WILDCAT NAME
Blanco Pictured Cliffs Ext.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 13, T-32-N, R-12-W, NMPM
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6382' GL

RECEIVED

NOV 09 1982

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(Do not report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-31-82 Tested surface casing, held 600#/30 minutes. TD 3105'. Ran 96 jts. 2 7/8", 6.4#, J-55 E production casing, 3084' set at 3097'. Baffle set at 3086'. Cemented with 1794 cu. ft. cement. WOC 18 hours. Top of cement at 600'.

11-4-82 Tested casing to 4000#, OK.

11-5-82 PBTD 3086'. Perf'd 2896', 2905', 2926', 2933', 2940', 2958', 2965', 2972', 2981', 2987', 3016', 3059' with 1 spz. Fraced with 78,000# 10/20 sand and 80,000 gal. treated water. Dropped 24 sets of 1 ball each. Flushed with 800 gal. water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Drilling Clerk DATE November 9, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, ANY _____

ACCEPTED FOR RECORD

NOV 24 1982

FARMINGTON DISTRICT