

SUNDRY NOTICES AND REPORTS ON WELLS

1. oil well ☒ gas well ☒ other

2. NAME OF OPERATOR
LOBO PRODUCTION

3. ADDRESS OF OPERATOR
P.O. Box 2364, Farmington, New Mex 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 935' FNL & 810' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other)

SUBSEQUENT REPORT OF:

(NOTE: Report results of multiple completion of zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

June 5, 1984- WOC.

June 6, 1984- Ran 54 jts. 5 1/2" 15.5# J-55 casing. Set at 4544'. Blew and cleaned up hole for 30 minutes.

Rigged up Halco to cement. Pumped 20 barrels 25# gel H2O spacer.

Pumped 150 sks 50/50 poz. and 2% gel with 10% salt and 6% Halad 9.

14# per gallon. Plug Down at 9:00am. Removed BOP and released rig.

June 8, 1984- Tallied 170 jts 2 3/8" 4.7# tubing. Tagged @ 4458'. Drilled cement to 4628', circulated clean. Ran GR, CCL and Bond logs from PBTD 4628'. Pressure tested casing and liner 3800psi. Circulated w/1% KCL H2O. Perfed Dakota 4625'-4445', 34 shots w/26 holes. Ran 5 1/2" PKR and set @ 4322'.

Subsurface Safety Valve: Manu. and Type _____ Sat @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *R. Claussen* TITLE Operator DATE 6-13-84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

ACCEPTED FOR RECORD

JUN 19 1984

FARMINGTON RESOURCE AREA

BV

NMOCC