

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Sundry Notices and Reports on Wells

ST FEB 25 AM 8:19

070 TALL, ACTON, NM

1. Type of Well
Gas

2. Name of Operator
Texas Pacific Oil & Gas Co., C/O Joseph E. Seagrams & Sons, Inc.

3. Address & Phone No. of Operator
800 3rd Ave., New York City, NY 10022-7699

4. Location of Well, Footage, Sec., T, R, M
1902' FSL and 688' FWL Sec. 21, T-32-N, R-17-W, NMPM
L

5. Lease Number
14-20-603-5012
6. If Indian, All. or
Tribe Name
Navajo
7. Unit Agreement Name
N/A
8. Well Name & Number
Navajo #18
9. API Well No.
30-045-2649600
10. Field and Pool
Many Rocks
11. County & State
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☒ Notice of Intent

☒ Abandonment

☐ Change of Plans

☐ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☐ Other -

13. Describe Proposed or Completed Operations

Texas Pacific Oil and Gas Co., proposes to Plug and Abandon this well per the attached procedure and diagram.

RECEIVED
MAR - 3 1997
OIL COOL. BUREAU
FILED

14. I hereby certify that the foregoing is true and correct.

Signed William F. Clark Title Contractor
William F. Clark, A-Plus Well Service

Date 2/24/97

(This space for Federal or State Office use)

APPROVED BY /S/ Duane W. Spencer Title _____ Date FEB 27 1997

CONDITION OF APPROVAL, if any:

NMOCD

Navajo #18

Proposed P&A

Many Rocks Gallup

1902'S, 688'W Sec 21, T-32-N, R-17-W, San Juan County, NM

Today's Date: 2/19/97

Spud: 11/25/85

Completed: 2/5/86

Point Lookout @ Surface

Gallup @1380'

Sanostee Lime @ 1734'

9" Hole

6-1/4" Hole

3-7/8" Hole

TD 1739'

7" 22# Casing Set @ 91'
Cmt with 9 cf (Circulated to Surface)

Perforate at 141'

Plug #3 141' - Surface
Cmt with 24 sxs Class B.

ACTUAL
TOC @ 1294' (CBL)

TOC @ 1344' (Calc, 100%)

TOC @ 1436' (Calc, 75%)

Plug #1 1739' - 1662'
Cmt with 48 sxs Class B
(50% excess, long plug)

4-1/2" 9.5# Csg @ 1712'
Cemented with 32 sxs (37 cf)

Gallup Open Hole Interval:
1717' - 1729'

Well History:

7" 22# surface csg set at 91' cemented to surface with 9 cf.

4-1/2" 9.5# csg set at 1712', cemented with 37 cf
TOC by CBL at 1294'.

Gallup zone open hole interval 1717' - 1729'.

2-3/8" tubing at 1729'.

Proposed Plugging Procedure:

1. Pull tubing. RIH and tag bottom. Plug #1 from 1739' to 1330' with 48 sxs Class B cement. POH with tubing.
2. WOC and then RIH and tag cement. Pressure test casing to 300#. POH and LD tubing.
3. Perforate 2 squeeze holes at 141'. Establish circulation out bradenhead. Mix and pump 24 sxs Class B cement from 141' to surface, circulate good cement out bradenhead.
4. WOC, cut off wellhead and install P&A marker.