submitted in lieu of Form 3160-5

RECEIVE

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT Sundry Notices and Reports on Wells

97 APR 21 MAY 9. 33

5. Lease Number 14-20-603-5012 1. Type of Well 6. If Indian, All. or Oil Tribe Name Navaio **Unit Agreement Name** 7. Texas Pacific Oil & Gas Co., C/O Joseph E. Seagram & Sons, Inc. Well Name & Number 8. 3. Address & Phone No. of Operator Navajo #18 800 3rd Ave., New York City, NY 10022-7699 API Well No. 9. 30-045-2649600 4. Location of Well, Footage, Sec., T, R, M 10. Field and Pool 1902' FSL and 688' FWL, Sec. 21, T-32-N, R-17-W, NMPM Many Rocks County & State 11. San Juan County, NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action ____ Notice of Intent X Abandonment Change of Plans ___ Recompletion New Construction Plugging Back Non-Routine Fracturing X Subsequent Report ___ Casing Repair _ Water Shut off ___ Altering Casing Conversion to Injection ____ Final Abandonment _ Other -13. Describe Proposed or Completed Operations Texas Pacific Oil & Gas Co., plugged and abandoned this well on April 9, 1997 per the attached Plug & Abandonment report. 14. I hereby certify that the foregoing is true and correct. Date 4/17/97 Contractor Signed_ William F. Clark, President A-Plus Well Service (This space for Federal or State Office use) ______Date_- • 1997 APPROVED BY 18/ Down W. Spencer Title CONDITION OF APPROVAL, if any:

A - PLUS WELL SERVICE, INC.

P.O. BOX 1979 FARMINGTON, NM 87499

505-325-2627 • FAX: 505-325-1211

Texas Pacific Oil & Gas Co., c/o Joseph E. Seagram & Sons Navajo #18 1902' FSL and 688' FWL Sec.21, T-32-N, R-17-W, San Juan County, NM BIA 14-20-603-5012

97 APR 21 AM 9A 5 1 16, 1997

070 FARMINGTON, NM

Plug & Abandonment Report

Cementing Summary:

Plug #1 with 48 sxs Class B cement with 2% CaCl, from 1729' to 1108' into Gallup perforations and over top.

Plug #2 with 90 sxs Class B cement pumped down 4-1/2" casing from 386' to surface, circulate good cement to surface.

Plugging Summary:

Notified BLM on 4/7/97

- 4-8-97 Safety Meeting. Road rig to location. Rig up. Open up well, no pressures. PU on tubing; found free. Install wellhead and BOP, NU. PU 1 joint tubing and RIH; tag bottom at 1739'. Plug #1 with 48 sxs Class B cement with 2% CaCl, from 1729' to 1108' into Gallup perforations and over top. POH to 1109'. Shut in well and WOC. RIH and tag cement at 1141'. Load casing with 2 bbls water and pressure test to 500#, held OK. POH and LD tubing. RIH and perforate 2 squeeze holes at 386'. POH and RD. Establish circulation down 4-1/2" casing and out 7-5/8" with 8 bbls water. Plug #2 with 90 sxs Class B cement pumped down 4-1/2" casing from 386' to surface, circulate good cement to surface. Shut in well and WOC. SFD.
- 4-9-97 Safety Meeting. Open up well. ND BOP and remove wellhead. Dig out wellhead. Cut wellhead off; found cement down 15' in 5" and 8-5/8" annulus. Mix 20 sxs Class B cement, fill casing and annulus; then install P&A marker. RD rig and equipment: prepare to move off location.
 - J. Sanchez, BLM representative was on location.