

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.
SF 078146 A

6. If Indian, Allottee or Tribe Name
NA

7. If Unit or CA, Agreement Designation
- NA

8. Well Name and No.
Horton Fed. CB-27 #1

9. API Well No.
30-045-28892

10. Field and Pool, or Exploratory Area
Basin Fruitland Coal

11. County or Parish, State
San Juan, NM

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Emerald Gas Operating Co.

3. Address and Telephone No.
570 Turner Drive, "B", Durango CO 81301 (303) 247-1500

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
NESW, 1934' FSL & 1794' FWL
K, Section 27, T32N-R12W, NMPM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION	
☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☐ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment Notice	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut-Off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other Commence drilling to	☐ Dispose Water
	topset depth	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- Spud well @ 11:30 a.m., 12-18-92. Drilled 12-1/4" hole to 333' KB. Ran 9-5/8", 36 #/ft, J-55 ST & C casing landed @ 328' KB. Cemented with 225 sx Class "B" with 3% CaCl₂. Good returns, circulate to surface. Plug down @ 8:00 p.m., 12-18-92.
- Drilled to topset TD of 2320' KB. Log well with GR-DIL. Loggers TD 2302' KB. Ran 7", 23# 1b/ft, K-55, LT & C casing landed at 2320' KB. Cemented with 250 sx 65-35 Pozmix, with 6% gel, 10% salt, and 6-1/4 lb/sk Gilsonite followed by 200 sx Class "B" with 3% salt and 6-1/4 lb/sk Gilsonite. Had good returns, circulate cement to surface. Plug down 4:30 a.m., 12-21-92. Release rig and wait on weather and cavitation rig to drill out, cavitate and complete.

RECEIVED
MAR 17 1993

OIL CON. DIV.

DIST. 3

RECEIVED
BLM
MAR 9 9 AM 10:58
FARMINGTON, NM

14. I hereby certify that the foregoing is true and correct

Signed Bruce Boyce

Title Mgr. of Geol. & Devel.

Date 3/8/93

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

ACCEPTED FOR RECORD

MAR 15 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOS

FARMINGTON DISTRICT OFFICE

ACCEPTED FOR RECORD

MAY 11 1933

LIBRARY OF THE

of