Form 3160-5 (Junc 1990)

Do not use

UNITED STATES DEPARTMENT OF THE INTERIOR 95 HAY 23 PH 2: 32

THE PROPERTY OF STREET

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No. 14-20-603-584

or Tribe Name

SUNDRY NOTICES AND REPORTS ON WHAT PARMING ON NAM	6. If Indian, Allotton
this form for proposals to drill or to deepen or reentry to a different reservoir.	
Use "APPLICATION FOR PERMIT—" for such proposals	Navajo

OSE ATTEINATION FOR FEMALE	Navajo
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well X Oil Gas Well Well Other	8. Well Name and No.
2. Name of Operator	Mesa Gallup #15
21st Century Investment Company	9. API Wall No.
3. Address and Telephone No. C/O Walsh Engr. & Prod. Corp.	
7415 E. Main Farmington, New Mexico 87402 505 327-4892	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	Mesa Gallup
2155'FSL & 1750'FWL	11. County or Parish, State
Section 14, T32N, R18W	San Juan Co., N.M.
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REP	ORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTIO)N

TYPE OF SUBMISSION	TIPE OF AC	HON
Notice of Intent DECE	Abandonment	Change of Plans
Subsequent Report MAY 3	0 1935 Plugging Back	New Construction Non-Routine Fracturing
	Casing Repair	Water Shut-Off Conversion to Injection
Final Abandonment Mogo [] []	No DIVOX Other See Below 1. 3	Dispose Water (Note: Report results of multiple completion on Well
פוש	no も	Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/6/95 TD 1625'. Ran 40 joints 5-1/2", 15.5# K-55, L & ST & C yellow band casing (1623.37') and set at 1623'GL., with 90 sx (185 cuft) of Class "B" with 2% metasilicate followed by 75 sx (89 cuft) of Class "B" with 2% CaCl2. Preceded cement with 30 bbls of gel water. Displaced plug with 39 bbls. Circulated 15 bbls of cement to surface.

Drill 4-3/4" hole to 1700'. Well will be completed naturally.

	ACCEPTED FOR RECORD		
		MAY 25 1995	
	FARM	INGTON DISTRICT OFFICE	
4. I hereby certify that the foregoing is true and correct Signed Paul C. Thomps	Paul C. Thompson, P.E.		
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Tide	Date	
Fille 18 U.S.C. Section 1001, makes it a crime for any person kn	owingly and willfully NAMOCD then or agency of the United	d States any false, fictitious of fraudulent state	