

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)

FORM APPROVED

OMB NO. 1004-0137

Expires: February 28, 1995

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐						5. LEASE DESIGNATION AND SERIAL NO. NM 019414	
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐						6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
2. NAME OF OPERATOR Cross Timbers Operating Company						7. UNIT AGREEMENT NAME	
3. ADDRESS AND TELEPHONE NO. 2700 Farmington Ave., Bldg. K. Ste 1 Farmington, NM 87401 505 324-1090						8. FARM OR LEASE NAME, WELL NO. STANOLIND GAS COM D #1B	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 875' FSL & 820' FEL At top prod. interval reported below At total depth						9. API WELL NO. 30-045-30841	
14. PERMIT NO.						DATE ISSUED	
15. DATE SPUDDED 12/1/01						10. FIELD AND POOL, OR WILDCAT BLANCO MESAVERDE	
16. DATE T.D. REACHED 12/27/01						11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC 17, T32N, R12W	
17. DATE COMPL.(Ready to prod.) 1/31/02						12. COUNTY OR PARISH San Juan	
18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 5991' GL 6003' KB						13. STATE NM	
20. TOTAL DEPTH, MD & TVD 4695'						19. ELEV. CASINGHEAD	
21. PLUG, BACK T.D., MD & TVD 4639'						23. INTERVALS DRILLED BY ROTARY TOOLS 0 - TD	
22. IF MULTIPLE COMPL., HOW MANY*						CABLE TOOLS	
24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)* MESAVERDE 4324' - 4586'						25. WAS DIRECTIONAL SURVEY MADE YES	
26. TYPE ELECTRIC AND OTHER LOGS RUN Array Ind/GR/SP/MSFL/CAL/TripLe Litho Density/CSN/Pe/CCL						27. WAS WELL CORED NO	
28. CASING RECORD (Report all strings set in well)							
CASING SIZE/GRADE		WEIGHT, LB./FT.		DEPTH SET (MD)		HOLE SIZE	
9-5/8" J-55		36#		194'		12-1/4"	
7" J-55		20#		2,110'		8-3/4"	
4-1/2" J-55		10.5#		4695'		6-1/4"	
29. LINER RECORD							
SIZE		TOP (MD)		BOTTOM (MD)		SACKS CEMENT*	
30. TUBING RECORD							
SIZE		TOP (MD)		BOTTOM (MD)		PACKER SET (MD)	
2-3/8"				4543'			
31. PERFORATION RECORD (Interval, size and number)							
MESAVERDE: 4586', 64', 57', 51', 46', 42', 36', 29', 21', 15', 07', 03', 4495', 91', 85', 80', 74', 68', 41', 33', 28', 23', 4336', 31', 24' (TTL 25 - 0.29" HOLES)							
32. ACID, SHOT, FRACTURE, CEMENT SOUFFEE, ETC.							
DEPTH INTERVAL (MD)				AMOUNT AND KIND OF MATERIAL USED			
4324' - 4586'				1500 gals 15% HCl acid, 153,191 gals 700 N2 foam & 152,580# 20/40 Brady sand			
33.* PRODUCTION							
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping - size and type of pump) FLOWING				WELL STATUS (Producing or shut-in) SI	
DATE OF TEST 2/1/02		HOURS TESTED 4		CHOKE SIZE 3/8"		PROD'N. FOR TEST PERIOD	
FLOW. TUBING PRESS. 600		CASING PRESSURE 640		CALCULATED 24-HOUR RATE		OIL - BBL. 0	
						GAS - MCF. 161	
						WATER - BBL. 12	
						GAS - OIL RATIO	
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold						TEST WITNESSED BY Jim Baker	
35. LIST OF ATTACHMENTS							
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records							
SIGNED		TITLE Operations Engineer				DATE 2/1/02	

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	GEOLOGIC MARKERS		
				NAME	MEAS. DEPTH	TRUE VERT. DEPTH
				Lower FTC	1768'	1768'
				Pictured Cliffs	1820'	1820'
				Cliffhouse SS	3560'	3560'
				Menefee	3741'	3741'
				Pt. Lookout	4460'	4460'