

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
ENERGEN RESOURCES CORPORATION

3. Address of Operator
2198 Bloomfield Highway, Farmington, NM 87401

4. Well Location
Unit Letter D : 1150 feet from the North line and 970 feet from the West line
Section 31 Township 32N Range 12W NMPM County San Juan

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
5868 GR

WELL API NO.

30-045-30887

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Calpepper Martin

8. Well No.

5B

9. Pool name or Wildcat

Blanco Mesaverde

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Spud @ 7:30 am 11/29/01. Drilled 12-1/4" hole to 240'. Ran 5 jts 9-5/8" 32.3# H-40 ST&C casing, set @ 233'. RU Halliburton. Cement with 150 sks Class B, 1/4#/sk flocele, 2% CaCl2 (177 cu.ft.) Plug down @ 6:45 am 11/30/01. Circulate 25 sks cement to surface. RD Halliburton. WOC. NU BOP. Test BOP & casing to 600 psi - ok.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Vicki Donaghey TITLE Production Assistant DATE 12/04/01

Type or print name Vicki Donaghey

Telephone No. 505-325-6800

(This space for State use)

APPROVED BY ORIGINAL SIGNED BY DANIEL T. PATTON

Conditions of approval, if any:

TITLE DEPT. OF ENERGY, MINERALS & NATURAL RESOURCES, DIST. 4 DATE DEC 11 2001

K