

NEW MEXICO OIL CONSERVATION COMMISSION
GAS WELL TEST DATA SHEET - - SAN JUAN BASIN

(TO BE USED FOR FRUITLAND, PICTURED CLIFFS, MESAVERDE, & ALL DAKOTA
EXCEPT BARKER DOME STORAGE AREA)

Pool Blenco Formation Mesa Verde County San Juan
Purchasing Pipeline El Paso Natural Gas Date Test Filed _____
Operator El Paso Natural Gas Lease Moore Well No. 6
Unit K Sec. 25 Twp. 32 Rge. 12 Pay Zone: From 5260 To 5494
Casing: OD 5 1/2 WT. 15.5 Set At 5484 Tubing: OD 2 WT. 4.7 T. Perf. 5363
Produced Through: Casing _____ Tubing X Gas Gravity: Measured .700 Estimated _____
Date of Flow Test: From 6/30/57 To 7/8/57 * Date S.I.P. Measured 4/4/57
Meter Run Size _____ Orifice Size _____ Type Chart _____ Type Taps _____

OBSERVED DATA

Flowing casing pressure (Dwt) _____ psig + 12 = _____ psia (a)
Flowing tubing pressure (Dwt) _____ psig + 12 = _____ psia (b)
Flowing meter pressure (Dwt) _____ psig + 12 = _____ psia (c)
Flowing meter pressure (meter reading when Dwt. measurement taken):
Normal chart reading _____ psig + 12 = _____ psia (d)
Square root chart reading (_____) ² x spring constant _____ = _____ psia (d)
Meter error (c) - (d) or (d) - (c) _____ ± _____ = _____ psi (e)
Friction loss, Flowing column to meter:
(b) - (c) Flow through tubing: (a) - (c) Flow through casing _____ = _____ psi (f)
Seven day average static meter pressure (from meter chart):
Normal chart average reading _____ psig + 12 = _____ psia (g)
Square root chart average reading (7.00) ² x sp. const. 10 = 490 psia (g)
Corrected seven day avge. meter press. (p_f) (g) + (e) = 490 psia (h)
P_t = (h) + (f) = 490 psia (i)
Wellhead casing shut-in pressure (Dwt) 1008 psig + 12 = 1020 psia (j)
Wellhead tubing shut-in pressure (Dwt) 1010 psig + 12 = 1022 psia (k)
P_c = (j) or (k) whichever well flowed through = 1022 psia (l)
Flowing Temp. (Meter Run) 80 °F + 460 = 540 °Abs (m)
P_d = 1/2 P_c = 1/2 (l) = 511 psia (n)

FLOW RATE CALCULATION

Q = _____ X $\left(\frac{\sqrt{(c)}}{\sqrt{(d)}} \right)^* = \underline{1528}$ MCF/da
(integrated)

DELIVERABILITY CALCULATION

D = Q 1528 $\left[\frac{P_c^2 - P_d^2}{P_c^2 - P_w^2} \right]^n = \underline{1571}$ MCF/da.
 $\frac{1.0374}{1.0279}$

SUMMARY

P_c = 1022 psia
Q = 1528 Mcf/day
P_w = 538 psia
P_d = 511 psia
D = 1571 Mcf/day

Company El Paso Natural Gas
By Original Signed
Title Lewis D. Galloway
Witnessed by _____
Company _____

* This is date of completion test.
* Meter error correction factor

REMARKS OR FRICTION CALCULATIONS

GL	(1-e ^{-S})	(F _c Q) ²	(F _c Q) ² (1-e ^{-S}) R ²	P _t ² (Column i)	P _t ² + R ²	P _w
<u>3754</u>	<u>.239</u>	<u>206.382</u>	<u>49,325</u>	<u>240,100</u>	<u>289,425</u>	<u>538</u>

D at 500 = 1496



