


STATE OF NEW MEXICO
OIL CONSERVATION
COMMISSION
DISTRICT NO. 3
Phone 99 P. O. Box 697
AZTEC, NEW MEXICO

(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office State
Lease No. 72260
Unit Surface Unit
Sec. No. 731

SUNDRY NOTICES AND REPORTS ON WELLS



NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Farmington, New Mexico, November 21, 1951

Well No. 8 is located 1650 ft. from N line and 1520 ft. from E line of sec. 28

1/4 of section 28 T-25-N R-9-W 114°W
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Oilfield San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6612 ft. (C.S.L.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well was drilled to a total depth of 3121 feet with outer 8 1/2" casing was set at 101 feet as previously reported. No production string casing has been run. The fractured Cliffs formation was not productive and a 150 sack cement plug was set with top at 1326 feet. Drill stem tests were then run to test the Jo Blama formation from 1326 feet to 1385 feet. The results of these drill stem tests showed the Jo Blama formation to be nonproductive of oil or gas and/or water. It is proposed to permanently abandon this well as follows: 1. Fill hole from 1326 feet to approximately 378 feet with 12-pound mud. 2. Plug hole with heavy duty solid cement necessary to fill hole from top of mud to surface of hole. 3. Erect 2" pipe and marker and restore ground level to original contours as per regulation.

ILLEGIBLE

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Standard Oil and Gas Company

Address Box 147

Farmington, New Mexico

By A. H. Gibson

Title State Geologist