


STATE OF NEW MEXICO  
OIL CONSERVATION  
COMMISSION  
DISTRICT NO. 3  
Phone 99 P. O. Box 697  
AZTEC, NEW MEXICO

(SUBMIT IN TRIPLICATE)  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Alamos  
Lease No. 1774  
Unit Las Alamos  
No. 98, 100, 101



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

San Juan, New Mexico, November 17, 1951

Well No. 7 is located 1600 ft. from [N] line and 1200 ft. from [E] line of sec. 14

15/4 of Section 14 (1/4 Sec. and Sec. No.) 1-10-51 (Twp.) 1-10-51 (Range) 2-10-51 (Meridian)  
Alamos (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6470 ft. ( )

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well was drilled to total depth of 2295 feet with rotary tools. A 5" casing was set at 2157 feet. Hole was cleaned out to total depth with cable tools. Unable to shoot well with 380 due to excessive water penetration. No shows of gas or oil on logs or by snatching. It is proposed to abandon this well and abandon hole as follows: 1. Plug hole with well cement from bottom of hole to point within 5" casing above isolated drifts formation; 2. Plug off casing above this point in order to recover casing; 3. Plug hole with 12 pound mud up to water level (approximately 150 feet); 4. Plug hole with quality solid cement necessary to fill hole from top of mud to surface of hole; 5. Treat 1' edge and surface and restore ground surface to original condition as per regulations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Las Alamos Oil and Gas Co., Inc.

Address Box 117

ILLEGIBLE

By A. W. Gibson

Title Geologist

..... 2000

..... 1999

..... 1998

EXTRACTED FROM THE 18  
SERIALS OF THE  
PROSECUTION OF THE  
CASE OF THE

SECRET NO DISSEM TO OTHER YACINUS

THE UNITED STATES OF AMERICA  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
WASHINGTON, D. C. 20250

THE UNIVERSITY OF MICHIGAN LIBRARY  
 100 TAPSCOTT DRIVE  
 ANN ARBOR, MICHIGAN 48106-1000  
 TEL: 734 763 1000  
 FAX: 734 763 1000  
 WWW: WWW.LIBRARY.MICHIGAN.EDU

\_\_\_\_\_ for oil \_\_\_\_\_ barrel \_\_\_\_\_

... *but* ...

ends with a zero digit  $0$  or a one digit  $1$ .

... and the ... ..

10. The defendant is a natural born citizen of the United States.

... ..

[illegible]