

COPY FOR
STATE OF NEW MEXICO
OIL CONSERVATION
COMMISSION
SUBMIT IN TRIPLICATE TO
DISTRICT OFFICE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 077936
Unit San Juan Unit

SUNDRY NOTICES AND REPORTS ON WELLS FEB 20 1952

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	<u>X</u>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Farmington, New Mexico, February 12, 1952

Well No. 1-3 is located 1900 ft. from N line and 1900 ft. from E line of sec. 1

SE/4, Section 1 T-36-N R-10-W NMPN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6540 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddling jobs, cementing points, and all other important proposed work)

Notice of Intention to Abandon Well, Form 9-331a was approved January 29, 1952. Well was permanently plugged and abandoned as follows: 1. Plugged hole with solid cement from bottom of hole to 2285 feet; 2. Shot 7" casing at following depths: at 1485 feet, at 1303 feet, at 1151 feet, at 1061 feet, at 943 feet, at 820 feet and at 791 feet. 7" casing was shot free at 943 feet and 791 feet of 7" casing was recovered; 3. Filled hole with 12 pound mud from 2285 feet to 430 feet; 4. Spotted 40 sacks cement plug from 430 to 305 feet; 5. Filled hole with 12 pound mud from 305 to 110 feet; 6. February 12, 1952, plugged hole with solid cement from 110 feet to surface of hole; 7. Erected 4' pipe marker and restored ground level to original contours as per regulations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Stanolind Oil and Gas Company

Address Box 487

Farmington, New Mexico

By L. D. Spurr, Jr.

Title Production Foreman

ILLEGIBLE