(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL		

	APP11 25 , 19 31						
Well No.2 Pipkin is lo	cated 990 ft.	from	and 1045 ft. from Fline o	of sec. 35			
NET Sec. 35	28N	11¥	N.X.P.W.				
(14 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)				
Kuts Canyon	San Jua	n	New Mexico				
(Field)	(Cou	nty or Subdivision)	(State or Territor	у)			

The elevation of the derrick floor above sea level is 5662 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Rotary drilled 7-7/8" hole to 1700. Top of P.C. at 1594. Set 1598 of 52" O.D. production pipe and cemented with 75 sacks using spacers, cement shoe and float collar. Bumped last plug with 900# pressure and held for 20 Min. Rotary off, spudder on and after 72 Hrs. drilled cement plug and cleaned hole. Deepened to 1705 with spudder, cleaned out and shot with 340 quarts solidified Mitro.

Company.	Potash	Company	of Am	erica		
		, Carlsba			0	
						I P. Corbin
	L. P. Co					Geologist