

## NEW MEXICO OIL CONSERVATION COMMISSION

## NOTICE OF INTENTION TO DRILL

See Rules 101 and 1104.

If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval.

Astec, New Mexico

November 10, 1952

Place

Date

Notice hereby is given that it is our intention to commence the drilling of a well to be known as

Minto-Kenaston


Madden-Selby

well No. 3 in NE/4

Company or Operator Lease  
of Sec. 20, T. 29N, R. 11W, N. M., P. M. Pulcher-Kuta Pool, San Juan County.

The well is 1080 feet from (N.) line and 940 feet from (E.) (W.) line of the above section.

(Give location from section lines. Cross out wrong directions.)



AREA 640 ACRES

LOCATE WELL CORRECTLY

If state land the oil and gas lease is No. Assignment No.

If patented land the owner is: Madden & Selby, 40 A.; Martin Ramirez, 40A  
Address Marie Mangum, 45 A.; Joseph Hartman, et al, 35 A.; Mangum

If government land the permittee is: A Hartman acreages far-out from Astec  
Address Oil & Gas Co., Dallas, Texas

The lessee is: Minto-Kenaston, Astec, N.M.

Address

We propose to drill well with drilling equipment as follows: Rotary tools.

The status of a bond for this well in conformance with Rule 101 of the General Rules and Regulations of the Commission is as follows: \$10,000 Blanket bond on file with the Commission.

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
9-7/8"	8-5/8"	30#	Second Hand	110'	Cemented	112
7-7/8"	5 1/2"	11#	"	900'	Cemented	200
				600'		

If changes in the above plans become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 300-600 feet.

Additional information: We propose to drill a well to and through the Farmington sandstone, estimated depth 900'. A minimum of 100' of 8-5/8" casing will be cemented to the surface, approximately 900' of 5 1/2" casing with approximately 200 sacks; drill the sand, and, if conditions warrant, approximately 600' of 5 1/2" casing with approximately 200 sacks; complete as an oil well.

Approved: Nov 15, 1952

except as follows:

Minto-Kenaston

Company or Operator

By

Position: General Manager

Send communications regarding well to:

Name: Bill W. Minto

Address: Box 471, Astec, New Mexico

OIL CONSERVATION COMMISSION

By: Emory C. Arnold  
Title: Oil & Gas Inspector, Dist. #3