

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLYSTANOLIND OIL AND GAS COMPANY
(Company or Operator)Gallegos Canyon Unit
(Lease)

Well No. 27, in NE $\frac{1}{4}$ of SW $\frac{1}{4}$, of Sec. 30, T. 29-N, R. 12-W, NMPM.
West Kutz-Pictured Cliffs Pool, San Juan County.

Well is 1650 feet from South line and 1650 feet from West line
of Section 30. If State Land the Oil and Gas Lease No. is _____

Drilling Commenced April 5, 19 53. Drilling was Completed April 30, 19 53

Name of Drilling Contractor Crow, Benson & Montin

Address Shreveport, Louisiana

Elevation above sea level at Top of Tubing Head 5365'. The information given is to be kept confidential until
Not confidential, 19 _____


OIL SANDS OR ZONES

Pictured Cliffs
No. 1, from 1240 to 1300 No. 4, from _____ to _____
Core Analysis and Electrical Survey
No. 2, from _____ to _____ No. 5, from _____ to _____
show water bearing.
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None (Rotary Drilled) to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.



CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
9-5/8"	32#	New	98	None			Surface Casing

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/4"	9-5/8"	95'	120	Circulated		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

NONE

Result of Production Stimulation _____

_____ Depth Cleaned Out _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 1300 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to Producing 19

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland 970
B. Salt	T. Montoya	T. Farmington 496
T. Yates	T. Simpson	T. Pictured Cliffs 1240
T. 7 Rivers	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	496	496	Shale with sand stringers				
496	510	14	Sand				
510	970	460	Shale				
970	1240	270	Shale and Coal				
1240	1300	60	Shaley Sand				

OIL CONSERVATION COMMISSION
FIELD DISTRICT OFFICE
FARMINGTON, NEW MEXICO
5
1
1
2
1

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

STANOLIND OIL AND GAS COMPANY
Company or Operator
Name
Farmington, New Mexico
October 4, 1955
Address Box 487, Farmington, New Mexico
Position or Title Field Superintendent