

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-70

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Southland Royalty Company	8. Farm or Lease Name McDaniel
3. Address of Operator P. O. Drawer 570, Farmington, New Mexico 87499	9. Well No. 1
4. Location of well UNIT LETTER <u>A</u> <u>230'</u> FEET FROM THE <u>FNL</u> LINE AND <u>280</u> FEET FROM THE <u>East</u> LINE, SECTION <u>19</u> TOWNSHIP <u>29N</u> RANGE <u>11W</u> NMPM.	10. Field and Pool, or Wildcat Fulcher Kutz P. C.
15. Elevation (Show whether DF, RT, GR, etc.) 5523' GL	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/02/84 MIRU Bedford on 8-2-84. Pulled 1" pipe. Established rate down 3-1/2" casing and pumped 80 sacks (94 cu.ft.) of cement with 3% CaCl₂. Displaced to 510'. Shot squeeze hole to 510'. Pumped 69 sacks (82 cu.ft.) of cement with 3% CaCl₂ with 41 sacks, squeezed out squeeze hole to cover Ojo Alamo at 336'. Cut off casing and dumped cement to fill to surface. Installed dry hole marker. Location cleaned up. Rel rig 8-2-84.

RECEIVED
AUG 03 1984
OIL CON. DIV.
DIST. 3

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Esther J. Gray TITLE Secretary DATE 8-07-84

APPROVED BY Original Signed by CHARLES GHOLSON TITLE DEPUTY COMMISSIONER DATE AUG 10 1984

CONDITIONS OF APPROVAL, IF ANY: