

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SF 078146

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
P. O. Box 990, Farmington, New Mexico 87401
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1185' N, 1040' W

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6100' GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Newberry

9. WELL NO.

2A (PGA)

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 34, T-32-N, R-12-W
NMPM

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was plugged and abandoned as follows on 1-21-77:


Spotted 75 sack cement plug from 4800-5123' with 50 sks squeezed through hole in 4 1/2" casing at 4840'.

Perfed 4 holes at 2750' and spotted 100 sk cement plug from 2250-2767' with 50 sks. squeezed through perfs.

Perfed 4 holes at 1000' and spotted 50 sk cement plug from 691-1021' with 25 sks. squeezed through perfs.

Perfed 4 holes at 300'. Established circulation out bradenhead. Spotted 50 sk cement plug from 157-300' with 38 sks displaced through perfs. Closed bradenhead valve during last 2 1/2" bbls of displacement-pressure zero.

Cut off wellhead. Installed dry hole marker with 10 sk cement plug at surface. Location is clean and ready for inspection.



FEB 14 1977

18. I hereby certify that the foregoing is true and correct

SIGNED

J. J. Duice

TITLE Drilling Clerk

DATE January 31, 1977

(This space is reserved for State Office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

JUN 8 1978

E. I. McGRATH

DISTRICT ENGINEER

P. J. McCall

*See Instructions on Reverse Side