

(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

PRINTED BY GOVERNMENT
(Other instructions on reverse side)

LEAD SHEET
Budget Bureau No. 42 R4424
5. LEASE DESIGNATION AND SERIAL NO.

SF 078146

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR El Paso Natural Gas Company		8. FARM OR LEASE NAME Newberry	
3. ADDRESS OF OPERATOR P. O. Box 990, Farmington, New Mexico 87401		9. WELL NO. 2A (PGA)	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1185' N, 1040' W		10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6100' GR	
		12. COUNTY OR PARISH San Juan	
		13. STATE New Mexico	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 34, T-32-N, R-12-W NMPM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was plugged and abandoned as follows on 1-21-77:


Spotted 75 sack cement plug from 4800'-5123' with 50 sks squeezed through hole in 4 1/2" casing at 4840'.

Perfed 4 holes at 2750' and spotted 100 sk cement plug from 2250-2767' with 50 sks. squeezed through perfs.

Perfed 4 holes at 1000' and spotted 50 sk cement plug from 691-1021' with 25 sks. squeezed through perfs.

Perfed 4 holes at 300'. Established circulation out bradenhead. Spotted 50 sk cement plug from 157-300' with 38 sks displaced through perfs. Closed bradenhead valve during last 2 1/2" bbls of displacement-pressure zero.

Cut off wellhead. Installed dry hole marker with 10 sk cement plug at surface. Location is clean and ready for inspection.



FEB 4 1977

18. I hereby certify that the foregoing is true and correct

SIGNED

J. G. Duico

TITLE Drilling Clerk

DATE January 31, 1977

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE