Form 9-331 (May 1963)

UNITED STATES SUBMIT IN TRIPLICATE* DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424 5. LEASE DESIGNATION AND SERIAL NO/

. 1,

SANTA FE 079511 GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS					6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDR (Do not use this form Us	Y NOII a for proposa e "APPLICA"	LES AND REP Is to drill or to deepe TION FOR PERMIT—"	ORIS ON n or plug back for such propo	WELLS to a different reservoir. sals.)			
OIL GAS X OTHER					7. UNIT AGREEMENT NAME Northeast Blanco Unit No. 1 Sec. 929		
2. NAME OF OPERATOR	8. FARM OR LEASE NA	8. FARM OR LEASE NAME					
Blackwood & Nichols Company					Northeast Blanco Unit		
3. ADDRESS OF OPERATOR					9. WELL NO.		
P.O. Box 1237, Durango, Colorado 81301					63- 5K		
4. LOCATION OF WELL (Report See also space 17 below.)	10. FIELD AND POOL, (R WILDCAT					
At surface	Blanco Mesave	erde					
350' F/SL - 1890' F/WL					SURVEY OR AREA	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
					SW/4 Sec. 13	3-30N-8W NMPM	
14. PERMIT NO.		15. ELEVATIONS (Show	whether DF, RT,	T, GR, etc.)	12. COUNTY OR PARISI	H 13. STATE	
		6073 GR			San Juan	New Mexico	
16.	Check Ap	propriate Box To I	ndicate Nati	re of Notice, Report, or	Other Data		
NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF		ULL OR ALTER CASING		WATER SHUT-OFF	X	WELL	
FRACTURE TREAT		ULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING (
SHOOT OR ACIDIZE		BANDON*		SHOOTING OR ACIDIZING	ABANDONME	NT*	
REPAIR WELL		HANGE PLANS		(Other)			
(Other)				(Note: Report resu	lts of multiple completion apletion Report and Log fo	on Well	
17. DESCRIBE PROPOSED OR CO proposed work. If we nent to this work.)*	MPLETED OPER	ATIONS (Clearly state ally drilled, give subs	all pertinent de urface location				
	, ran s	ix jts., 9-5/8	8", 32.30	#, H-40 casing.	270' set at 287	cemented	
				m chloride, cemen			
tested casing v							
2120'. Cementer with 100 sacks from first stage 12½# Gilsonite 7-12-75 tested 2120', tested controllers.	ed first class B ge. Cem per sac casing casing w	stage with 80, with 2% calcented second accordance with 1200 PSI at 1200 PSI a	O sacks H cium chlo stage wit d 20 bbls for thre for thirt	94' set at 3308' owco Lite class B ride. Did not ci h 300 sacks Howco. cement to surfa e minutes, held 0 y minutes, held 0	cement with 6% rculate any ceme Lite class B conce on second state. Drilled DV to K.	Gel, followed ent to surface ement with age. On tool at	
)-50 Poz	mix with 4% G		casing, 5592' set ½# Gilsonite per			
On 7-16-75, tes	sted 4½"	casing with	2000 PSI	for 20 minutes.	Held O.K.		
Place MO)	foregoing is	true and correct		NO.	1	29 1975 CON. COM.	
(This space for Federal	or State offic	e use)	•				
APPROVED BYCONDITIONS OF APPR	OVAL, IF A		ITLE		DATE		